

**3rd Generation Partnership Project;  
Technical Specification Group Radio Access Network;  
3GPP TS 38.522 V16.2.0 (2019-12) NR;  
~~User Equipment (UE) conformance specification;~~  
Applicability of radio transmission, radio reception and radio  
resource management test cases  
(Release 16)**

---



Keywords  
NR, radio

---

### **3GPP**

Postal address

---

3GPP support office address

---

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

---

<http://www.3gpp.org>

### **Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© 2019, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).  
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members  
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
GSM® and the GSM logo are registered and owned by the GSM Association

---

---

# Contents

Foreword.....	4
1 Scope.....	5
2 References.....	5
3 Definitions, symbols and abbreviations.....	6
3.1 Definitions.....	6
3.2 Symbols.....	6
3.3 Abbreviations.....	7
4 Recommended test case applicability.....	7
4.1 RF conformance test cases.....	8
4.1.1 FR1 standalone conformance test cases.....	9
4.1.2 FR2 standalone conformance test cases.....	16
4.1.3 NR interworking between NR FR1 and NR FR2 and between NR and LTE conformance test cases .....	19
4.1.4 Performance conformance test cases.....	46
4.2 RRM conformance test cases.....	50
<b>Annex A (informative): FFS.....</b>	<b>65</b>
Annex B (informative): Change history.....	66

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

The present document is one part of a multi-part Technical Specification (TS) covering the New Radio (NR) User Equipment (UE) conformance specification, which is divided in the following parts:

3GPP TS 38.521-1 [1]: NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Range 1 Standalone;

3GPP TS 38.521-2 [2]: NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 2: Range 2 Standalone;

3GPP TS 38.521-3 [3]: NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios;

3GPP TS 38.521-4 [4]: NR; User Equipment conformance specification; Radio transmission and reception; Part 4: Performance;

**3GPP TS 38.522: NR; User Equipment (UE) conformance specification; Applicability of RF and RRM test cases;**

3GPP TS 38.533 [5]: NR; User Equipment (UE) conformance specification; Radio resource management;

---

# 1 Scope

The present document provides the Implementation Conformance Statement (ICS) proforma for 5G New Radio (NR) User Equipment (UE), in compliance with the relevant requirements.

The present document specifies the recommended applicability statement for the test cases included in 3GPP TS 38.521-1 [1], TS 38.521-2 [2], TS 38.521-3 [3], TS 38.521-4 [4] and TS 38.533 [5]. These applicability statements are based on the features implemented in the UE.

Special conformance testing functions can be found in 3GPP TS 38.509 [6] and the common test environments are included in 3GPP TS 38.508-1 [7]. Common implementation conformance statement (ICS) proforma can be found in 3GPP TS 38.508-2 [8].

The present document is valid for UE implemented according to 3GPP releases starting from Release 15 up to the Release indicated on the cover page of the present document.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document unless the context in which the reference is made suggests a different Release is relevant (information on the applicable release in a particular context can be found in e.g. test case title, description or applicability, message description or content).

- [1] 3GPP TS 38.521-1: NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Range 1 Standalone
- [2] 3GPP TS 38.521-2: NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 2: Range 2 Standalone
- [3] 3GPP TS 38.521-3: NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios
- [4] 3GPP TS 38.521-4: NR; User Equipment conformance specification; Radio transmission and reception; Part 4: Performance
- [5] 3GPP TS 38.533: NR; User Equipment (UE) conformance specification; Radio resource management
- [6] 3GPP TS 38.509: 5GS; Special conformance testing functions for User Equipment (UE)
- [7] 3GPP TS 38.508-1: 5GS; User Equipment (UE) conformance specification; Part 1: Common test environment
- [8] 3GPP TS 38.508-2: 5GS; User Equipment (UE) conformance specification; Part 2: Common Implementation Conformance Statement (ICS) proforma
- [9] 3GPP TR 21.905: Vocabulary for 3GPP Specifications
- [10] 3GPP TS 36.521-2: Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) conformance specification; Radio transmission and reception; Part 2: Implementation Conformance Statement (ICS)

[11] 3GPP TS 38.331: "NR; Radio Resource Control (RRC) protocol specification".

Editor's note: More specifications need to be added.

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [9] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [9].

**EIRP(Link=Link angle, Meas=Link angle):** measurement of the UE such that the link angle is aligned with the measurement angle. EIRP (indicator to be measured) can be replaced by EIS, Frequency, EVM, carrier Leakage, In-band emission and OBW. Beam peak search grids, TX beam peak direction, and RX beam peak direction can be selected to describe Link.

**EIRP(Link=Link angle, Meas=beam peak direction):** measurement of the EIRP of the UE such that the measurement angle is aligned with the beam peak direction within an acceptable measurement error uncertainty.

**Implementation Conformance Statement (ICS):** statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented

**ICS proforma:** document, in the form of a questionnaire, which when completed for an implementation or system becomes an ICS

**Implementation extra Information for Testing (IXIT):** A statement made by a supplier or implementer of an UEUT which contains or references all of the information (in addition to that given in the ICS) related to the UEUT and its testing environment, which will enable the test laboratory to run an appropriate test suite against the UEUT

**Inter-band carrier aggregation:** Carrier aggregation of component carriers in different operating bands.

NOTE: Carriers aggregated in each band can be contiguous or non-contiguous.

**Intra-band contiguous carrier aggregation:** Contiguous carriers aggregated in the same operating band.

**Intra-band non-contiguous carrier aggregation:** Non-contiguous carriers aggregated in the same operating band.

**IXIT proforma:** A document, in the form of a questionnaire, which when completed for an UEUT becomes an IXIT

**Protocol Implementation Conformance Statement (PICS):** An ICS for an implementation or system claimed to conform to a given protocol specification

**Protocol Implementation eXtra Information for Testing (PIXIT):** An IXIT related to testing for conformance to a given protocol specification

**Static conformance review:** A review of the extent to which the static conformance requirements are claimed to be supported by the UEUT, by comparing the answers in the ICS(s) with the static conformance requirements expressed in the relevant specification(s)

**TRP(Link=Link angle):** measurement of the TRP of the UE such that the measurement angle is aligned with the beam peak direction within an acceptable measurement uncertainty. TX beam peak direction and RX beam peak direction can be selected to describe Link.

NOTE: For requirements based on EIRP/EIS, the radiated interface boundary is associated to the far-field region

### 3.2 Symbols

For the purposes of the present document, the following symbols apply:

<symbol> <Explanation>

### 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [9] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [9].

For the purposes of the present document, the following abbreviations apply:

CA	Carrier Aggregation
EN-DC	E-UTRA NR-Dual Connection
FR1	Frequency Range 1 (410 MHz - 7125 MHz)
FR2	Frequency Range 2 (24250 MHz - 52600 MHz)
ICS	Implementation Conformance Statement
IXIT	Implementation eXtra Information for Testing
NR	New Radio
PIXIT	Protocol Implementation eXtra Information for Testing
SCS	System Conformance Statement
SUL	Supplementary UpLink
TC	Test Case
TRP	Total Radiated Power
UEUT	User Equipment Under Test

---

## 4 Recommended test case applicability

The applicability of each individual test is identified in the tables 4.1.1-1 / 4.1.2-1 / 4.1.3-1 / 4.1.4-1 / 4.2-1. This is just a recommendation based on the purpose for which the test case was written.

The applicability of every test is formally expressed by the use of Boolean expressions that are based on parameters (ICS). The parameters (ICS) included in TS 38.508-2 [8] are used in the test case applicability condition without reference. Parameters (ICS) specified in 3GPP TS 36.521-2 [10] shall be referred with proper reference.

Selection criteria of tested bands and tested CA configurations for each applicable test is formally expressed using group theory based on parameters (ICS) included in annex A of TS 38.508-2 [8] without reference.

Additional information related to the Test Case (TC), e.g. affecting its dynamic behaviour or its execution may be provided as well.

The columns in tables 4.1.1-1 / 4.1.2-1 / 4.1.3-1 / 4.1.4-1 / 4.2-1 have the following meaning:

#### Clause

The clause column indicates the clause number in TS 38.521-1 [1], TS 38.521-2 [2], TS 38.521-3 [3], TS 38.521-4 [4] and TS 38.533 [5] that contains the test body.

#### Title

The title column describes the name of the test and contains the clause title of the clause in TS 38.521-1 [1], TS 38.521-2 [2], TS 38.521-3 [3], TS 38.521-4 [4] and TS 38.533 [5] that contains the test body.

#### Release

The release column indicates the earliest release from which each test case is applicable. It may also indicate a range of releases or a single release to which a test case is applicable.

#### Applicability - Condition

The following notations are used for the applicability column:

R	recommended - the test case is recommended to all terminals supporting NR
O	optional - the test case is optional

N/A	not applicable - in the given context, the test case is not recommended.
Ci	conditional - the test is recommended ("R") or not ("N/A") depending on the support of other items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table. For nested conditional expressions, the syntax "IF ... THEN (IF ... THEN ... ELSE...) ELSE ..." is used to avoid ambiguities.

#### Applicability - Comments

This comments column contains a verbal description of the condition included in the applicability column.

#### Tested Bands / CA-Configurations Selection

This column defines a set of bands / CA Configurations the test is to be run for, if the test is applicable. If the set is empty, the test is considered as not applicable.

The following notations are used in the tested bands selection column:

Di	Derive the set based on Band Selection Criteria Di defined in tables 4.1.1-1b, 4.1.2-1b, 4.1.3-1b, 4.1.4-1b.
Ei	Derive the set based on CA Configurations Selection Criteria Ei defined in tables 4.1.1-1c, 4.1.2-1c, 4.1.3-1c.
TBD	Band selection not defined at this time, in the meantime test all Bands / CA Configurations
Text	For more complex selection criteria, or if the criteria are already specified somewhere else in the spec, text reference to the section is given.

#### Additional Information

This column contains indication if the test case may perform differently depending on the UE capabilities and the measurement execution.

NOTE 1: To meet the validation requirements from certification bodies then there is a need to uniquely reference the FDD and TDD branch (i.e. different behaviour within one and the same TC) of common FDD and TDD RF test cases in table 4.1-1. The FDD and TDD branches of common FDD and TDD test cases can be referenced by amending a "FDD" or "TDD" suffix to the test case clause number.

**Editor's note: The above description will be updated when necessary, for example 1Tx and 2Tx differentiation.**

## 4.1 RF conformance test cases

NOTE: To determine applicability of a test case, supported CBW and SCS in the *RF-Parameters* IE (see TS 38.331 [11]) which conveys RF related capabilities for NR operation is taken into account.



## 4.1.1 FR1 standalone conformance test cases

Table 4.1.1-1: Applicability of RF SA FR1 conformance test cases, ref. TS 38.521-1 [1]

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
<b>6</b>	<b>Transmitter Characteristics</b>					
6.2.1	UE maximum output power	Rel-15	FR1_C01	UEs supporting 5GS NR FR1 PC3	FR1_D01	PC3 requirements applied
				UEs supporting 5GS NR FR1 PC2	FR1_D02	PC2 requirements applied
6.2.2	Maximum Power Reduction (MPR)	Rel-15	FR1_C01	UEs supporting 5GS FR1 PC3	FR1_D01	PC3 requirements applied Test execution is not necessary if TS 38.521-1 6.5.2.4.1 is executed.
				UEs supporting 5GS FR1 PC2	FR1_D02	PC2 requirements applied Test execution is not necessary if TS 38.521-1 6.5.2.4.1 is executed.
6.2.3	UE additional maximum output power reduction	Rel-15	FR1_C01	UEs supporting 5GS FR1 PC3	FR1_D01	PC3 requirements applied Test execution is not necessary if TS 38.521-1 6.5.2.3 and 6.5.3.3 are executed.
				UEs supporting 5GS FR1 PC2	FR1_D02	PC2 requirements applied Test execution is not necessary if TS 38.521-1 6.5.2.3 and 6.5.3.3 are executed.
6.2.4	Configured transmitted power	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.2A.1.1	UE maximum output power for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.2C.1	Configured transmitted power for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.2C.3	UE maximum output power for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.2C.4	UE maximum output power reduction for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.2C.5	UE additional maximum output power reduction for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.2D.1	UE maximum output power for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	Maximum Output Power for UL-MIMO is tested as part of the MPR test case with using MPR=1.5dB suggested by RAN4.
6.2D.2	UE maximum output power reduction for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	Test execution is not necessary if TS 38.521-1 6.5D.2.4.1 is executed.
6.2D.3	UE additional maximum output power reduction for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	Test execution is not necessary if TS 38.521-1 6.5D.2.3 and 6.5D.3.3 are executed.
6.2D.4	Configured transmitted power for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.3.1	Minimum output power	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.3.3.2	General ON/OFF time mask	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.3.3.4	PRACH time mask	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.3.3.6	SRS time mask	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.3.4.2	Absolute power tolerance	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	NOTE 1
6.3.4.3	Relative power tolerance	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.3.4.4	Aggregate power tolerance	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	NOTE 1
6.3A.1.1	Minimum output power for CA (2UL CA)	Rel-15	FR1_C04	UEs supporting 5GS FR1 and CA (2UL CA)	FR1_D01	
6.3A.3.1	Transmit ON/OFF time mask for CA (2UL CA)	Rel-15	FR1_C04	UEs supporting 5GS FR1 and CA (2UL CA)	FR1_D01	
6.3D.1	Minimum output power for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.3D.3	Transmit ON/OFF time mask for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.3D.4.1	Absolute power tolerance for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.3D.4.2	Relative power tolerance for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.3D.4.3	Aggregate power tolerance for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.4.1	Frequency error	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.4.2.1	Error Vector Magnitude	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.4.2.2	Carrier leakage	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.4.2.3	In-band emissions	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.4.2.4	EVM equalizer spectrum flatness	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.4.2.5	EVM equalizer spectrum flatness for Pi/2 BPSK	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.4A.1.1	Frequency error for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.4A.2.1.1	Error Vector Magnitude for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.4A.2.2.1	Carrier leakage for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.4A.2.3.1	In-band emissions for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.4C.1	Frequency error for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.4C.2.1	Error Vector Magnitude for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.4C.2.2	Carrier leakage for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.4C.2.3	In-band emissions for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.4C.2.4	EVM equalizer spectrum flatness for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.4D.1	Frequency error for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.4D.2.1	Error Vector Magnitude for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.4D.2.2	Carrier leakage for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.4D.2.3	In-band emissions for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.4D.2.4	EVM equalizer spectrum flatness for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.4D.3	Time alignment error for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.4D.4	Requirements for coherent UL MIMO	FFS	FFS	FFS	FFS	NOTE 1
6.5.1	Occupied bandwidth	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.5.2.2	Spectrum Emission Mask	Rel-15	FR1_C01	UEs supporting 5GS FR1 PC3	FR1_D01	PC3 requirements applied
				UEs supporting 5GS FR1 PC2	FR1_D02	PC2 requirements applied
6.5.2.3	Additional spectrum emission mask	Rel-15	FR1_C01	UEs supporting 5GS FR1 PC3	FR1_D01	NOTE 1 PC3 requirements applied
				UEs supporting 5GS FR1 PC2	FR1_D02	NOTE 1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						PC2 requirements applied

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5.2.4.1	NR ACLR	Rel-15	FR1_C01	UEs supporting 5GS FR1 PC3	FR1_D01	PC3 requirements applied
				UEs supporting 5GS FR1 PC2	FR1_D02	PC2 requirements applied
6.5.2.4.2	UTRA ACLR	Rel-15	FR1_C01	UEs supporting 5GS FR1 PC3	FR1_D01	PC3 requirements applied
6.5.3.1	General spurious emissions	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.5.3.2	Spurious emission for UE co-existence	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.5.3.3	Additional spurious emissions	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.5.4	Transmit intermodulation	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
6.5A.1.1	Occupied bandwidth for CA (2UL CA)	Rel-15	FR1_C04	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.5A.2.2.1	Spectrum emission mask for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.5A.2.4.1.1	NR ACLR for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.5A.2.4.2.1	UTRA ACLR for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.5A.3.1.1	General spurious emissions for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.5A.3.2.1	Spurious emissions for UE co-existence for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.5A.4.1	Transmit intermodulation for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2UL CA)	FFS	NOTE 1
6.5C.1	Occupied bandwidth for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.2.2	Spectrum Emission Mask for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.2.3	Additional spectrum emission mask for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.2.4.1	NR ACLR for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.2.4.2	UTRA ACLR for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.3.1	General spurious emissions for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.3.2	Spurious emission for UE co-existence for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.3.3	Additional spurious emissions for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5C.4	Transmit intermodulation for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
6.5D.1	Occupied bandwidth for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.5D.2.2	Spectrum Emission Mask for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.5D.2.3	Additional spectrum emission mask for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.5D.2.4.1	NR ACLR for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-	FR1_D01	

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
				MIMO		

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5D.2.4.2	UTRA ACLR for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.5D.3.1	General spurious emissions for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.5D.3.2	Spurious emission for UE co-existence for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.5D.3.3	Additional spurious emissions for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
6.5D.4	Transmit intermodulation for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
<b>7</b>	<b>Receiver Characteristics</b>					
7.3.2	Reference sensitivity power level	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
7.3A.1	Reference sensitivity power level for 2DL CA	FFS	FFS	FFS	FFS	NOTE 1
7.3A.2	Reference sensitivity level for CA (3DL CA)	FFS	FFS	FFS	FFS	NOTE 1
7.3A.3	Reference sensitivity level for CA (4DL CA)	FFS	FFS	FFS	FFS	NOTE 1
7.3C.2	Reference sensitivity power level for SUL	Rel-15	FR1_C02	UEs supporting 5GS FR1 and SUL	FR1_D03	NOTE 1
7.3D.2	Reference sensitivity power level for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
7.4	Maximum input level	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
7.4A.1	Maximum input level for CA (2DL CA)	FFS	FFS	FFS	FFS	NOTE 1
7.4A.2	Maximum input level for CA (3DL CA)	FFS	FFS	FFS	FFS	NOTE 1
7.4A.3	Maximum input level for CA (4DL CA)	FFS	FFS	FFS	FFS	NOTE 1
7.4D	Maximum input level for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
7.5	Adjacent channel selectivity	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	NOTE 1
7.5A.1	Adjacent channel selectivity for 2DL CA	FFS	FFS	FFS	FFS	NOTE 1
7.5A.2	Adjacent channel selectivity for 3DL CA	FFS	FFS	FFS	FFS	NOTE 1
7.5A.3	Adjacent channel selectivity for 4DL CA	FFS	FFS	FFS	FFS	NOTE 1
7.5D	Adjacent channel selectivity for UL-MIMO	FFS	FFS	FFS	FFS	
7.6.2	Inband Blocking	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
7.6.3	Out-of-band blocking	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
7.6.4	Narrow band blocking	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D04	
7.6D.2	Inband blocking for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
7.6D.3	Out-of-band blocking for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
7.6D.4	Narrow band blocking for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
7.7	Spurious response	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
7.7A.1	Spurious response for CA (2DL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (2DL CA)	FFS	NOTE 1
7.7A.2	Spurious response for CA (3DL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (3DL CA)	FFS	NOTE 1
7.7A.3	Spurious response for CA (4DL CA)	Rel-15	FFS	UEs supporting 5GS FR1 and CA (4DL CA)	FFS	NOTE 1
7.7D	Spurious response for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
7.8.2	Wide band Intermodulation	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
7.8D.2	Wide band Intermodulation for UL-MIMO	Rel-15	FR1_C03	UEs supporting 5GS FR1 and UL-MIMO	FR1_D01	
7.9	Spurious emissions	Rel-15	FR1_C01	UEs supporting 5GS FR1	FR1_D01	
7.9A.1	Spurious emission for 2DL CA	Rel-15	FR1_C05	UEs supporting 5GS FR1 and inter-band 2DL CA with a DL-only band	FR1_E02	

NOTE 1: The test case is incomplete.



**Table 4.1.1-1a: Applicability of RF SA FR1 conformance test cases Conditions**

FR1_C01	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/1 THEN R ELSE N/A
FR1_C02	IF (A.4.1-1/1 OR A.4.1-1/2) AND (A.4.1-2/3 OR A.4.1-2/5) AND A.4.1-3/1 THEN R ELSE N/A
FR1_C03	IF (A.4.1-1/1 OR A.4.1-1/2) AND (A.4.3.2-1/14 OR A.4.3.2-1/15) AND A.4.1-3/1 THEN R ELSE N/A
FR1_C04	IF (A.4.1-1/1 OR A.4.1-1/2) AND (A.4.1-4A/1 OR A.4.1-4A/2 OR A.4.1-4A/5) AND A.4.3.2A.1-2/1 AND A.4.1-3/1 THEN R ELSE N/A
FR1_C05	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-4A/5 AND A.4.1-2/4 AND A.4.3.2A.1-1/1 AND A.4.1-3/1 THEN R ELSE N/A
NOTE 1: The ICS proforma are defined in TS 38.508-2 [8] unless otherwise stated.	

**Table 4.1.1-1b: Tested Bands Selection Criteria for RF SA FR1 conformance test cases**

Code	Selection	Comment
D01	A.4.3.1-1 OR A.4.3.1-2	All supported FR1 Bands without SUL/SDL bands
D02	A.4.3.1-4	All supported FR1 PC2 Bands
D03	A.4.3.1-5	All supported FR1 SUL Bands
FR1_D04	{1,2,3,5,7,8,12,20,25,28,34,38,39,40,41,50,51,56,66,70,71,74,75,76}	UE supported bands among n1,n2,n3,n5,n7,n8,n12,n20,n25,n28,n34,n38,n39,n40,n41,n50,n51,n66,n70,n71,n74,n75,n76
<p>NOTE 1: Band Selection is based on set theory. For each feature, item number shall correspond to the Band number. The result is the set of bands for which the test shall be conducted. The following operators are used:</p> <p>AND: Set intersection (<math>\cap</math>). {1,2} AND {2,3} = {2}</p> <p>OR: Set union (<math>\cup</math>). {1,2} OR {2,3} = {1,2,3}</p> <p>NOT: Set complement (<math>\setminus</math>), full set being all bands. NOT{1} = {2 ...256}</p> <p>Also note that this is set without repetitions so {1} AND {1} = {1}</p> <p>The following basic sets are used:</p> <p>{1,2}: Explicitly given band set</p> <p>10MHz: All bands supporting 10 MHz</p> <p>The following sets derived from pro-forma tables are also used:</p> <p>TBD</p>		

**Table 4.1.1-1c: Tested CA Configurations Selection Criteria for RF SA FR1 conformance test cases**

	Selection	Comment
E01	A.4.3.2A.2.1-3 AND CARRIER_NO(2) AND NOT UL(A.4.3.2A.2.1-2)	All supported intra-band contiguous CA Configurations with 2 carriers in DL but no CA in UL
02	A.4.3.2A.4.1-1 AND CARRIER_NO(2) AND NOT UL(A.4.3.2A.4.1-2)	All supported inter-band CA Configurations with 2 carriers in DL but no CA in UL

## 4.1.2

## FR2 standalone conformance test cases

Table 4.1.2-1: Applicability of RF SA FR2 conformance test cases, ref. TS 38.521-2 [2]

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information (NOTE 3)
			Condition	Comment		
6.2.1.1	UE maximum output power - EIRP and TRP	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 4
6.2.1.2	UE maximum output power - Spherical coverage	Rel-15	FR2_C02	UEs supporting 5GS FR2 and beam correspondence without UL beam sweeping	FR2_D01	NOTE 1 NOTE 4
6.2.2	UE maximum output power reduction	FFS	FFS	FFS		NOTE 1
6.2.3	UE maximum output power with additional requirements	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.2A.1.1.1	UE maximum output power - EIRP and TRP for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.2A.1.1.2	UE maximum output power - EIRP and TRP for CA (3UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.2A.1.1.3	UE maximum output power - EIRP and TRP for CA (4UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.3.1	Minimum output power	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.3.2	Transmit OFF power	FFS	FFS	FFS	FFS	NOTE 1
6.3.3.2	General ON/OFF time mask	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.3.3.4	PRACH time mask	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.3.4.2	Absolute power tolerance	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.3.4.3	Relative power tolerance	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.3.4.4	Aggregate power tolerance	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.3A.1.1	Minimum output power for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.3A.2.1	Transmit OFF power for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.3A.2.2	Transmit OFF power for CA (3UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.3A.2.3	Transmit OFF power for CA (4UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.3D.3.4	SRS time mask for UL-MIMO	FFS	FFS	FFS	FFS	NOTE 1
6.4.1	Frequency error	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	
6.4.2.1	Error vector magnitude	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.4.2.2	Carrier leakage	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.4.2.3	In-band emissions	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.4.2.4	EVM equalizer spectrum flatness	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.4.2.5	EVM spectral flatness for pi/2 BPSK modulation	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information (NOTE 3)
			Condition	Comment		
6.4A.1.1	Frequency error for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.4A.1.2	Frequency error for CA (3UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.4A.1.3	Frequency error for CA (4UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.4A.2.3.1	In-band emissions for CA (2UL CA)	Rel-15	FFS	UEs supporting 5GS FR2 CA (2UL CA)	FFS	NOTE 1
6.5.1	Occupied bandwidth	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.5.2.1	Spectrum Emission Mask	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	
6.5.2.3	Adjacent channel leakage ratio	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.5.3.1	Transmitter Spurious emissions	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
6.5.3.2	Spurious emission band UE co-existence	FFS	FFS	FFS	FFS	NOTE 1
6.5A.1.1	Occupied bandwidth for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.1.2	Occupied bandwidth for CA (3UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.1.3	Occupied bandwidth for CA (4UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.2.1.1	Spectrum Emission Mask for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.2.1.2	Spectrum Emission Mask for CA (3UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.2.1.3	Spectrum Emission Mask for CA (4UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.2.2.1	Adjacent channel leakage ratio for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.2.2.2	Adjacent channel leakage ratio for CA (3UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.2.2.3	Adjacent channel leakage ratio for CA (4UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.3.1.1	Transmitter Spurious emissions for CA (2UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.3.1.2	Transmitter Spurious emissions for CA (3UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.5A.3.1.3	Transmitter Spurious emissions for CA (4UL CA)	FFS	FFS	FFS	FFS	NOTE 1
6.6	Beam correspondence	Rel-15	FR2_C03	UEs supporting 5GS FR2 and not beam correspondence without UL beam sweeping	FR2_D01	NOTE 1
<b>7</b>	<b>Receiver Characteristics</b>					
7.3.2	Reference sensitivity power level	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	
7.3.4	EIS spherical coverage	FFS	FFS	FFS	FFS	NOTE 1
7.4	Maximum input level	Rel-15	N/A	not recommended due to testability issues (NOTE 2)	N/A	NOTE 1
7.5	Adjacent channel selectivity	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
7.6.2	In-band Blocking	Rel-15	FR2_C01	UEs supporting 5GS FR2	FR2_D01	NOTE 1
NOTE 1: The test case is incomplete.						
NOTE 2: The test case applicability is set to N/A until the related testability issues are resolved.						
NOTE 3: For conformance testing involving FR2 test cases, the UE under test shall disable UL Tx diversity schemes.						
NOTE 4: All Power Class 3 UE supported bands needs to be tested to ensure the multiband relaxation declaration is compliant.						

**Table 4.1.2-1a: Applicability of RF SA FR2 conformance test cases Conditions**

FR2_C01 IF A.4.1-1/2 AND A.4.1-3/1 THEN R ELSE N/A
FR2_C02 IF A.4.1-1/2 AND A.4.1-3/1 AND A.4.3.2-1/XX THEN R ELSE N/A
FR2_C03 IF A.4.1-1/2 AND A.4.1-3/1 AND NOT(A.4.3.2-1/XX) THEN R ELSE N/A
NOTE 1: : The ICS proforma are defined in TS 38.508-2 [8] unless otherwise stated.

**Table 4.1.2-1b: Tested Bands Selection Criteria**

Code	Selection	Comment
FR2_D01	A.4.3.1-3	All supported FR2 Bands
<p>NOTE 1: Band Selection is based on set theory. For each feature, item number shall correspond to the Band number. The result is the set of bands for which the test shall be conducted. The following operators are used:</p> <p>AND: Set intersection (<math>\cap</math>). {1,2} AND {2,3} = {2}</p> <p>OR: Set union (<math>\cup</math>). {1,2} OR {2,3} = {1,2,3}</p> <p>NOT: Set complement (<math>\setminus</math>), full set being all bands. NOT{1} = {2 ...256}</p> <p>Also note that this is set without repetitions so {1} AND {1} = {1}</p> <p>The following basic sets are used:</p> <p>{1,2}: Explicitly given band set</p> <p>10MHz: All bands supporting 10 MHz</p> <p>The following sets derived from pro-forma tables are also used:</p> <p>TBD</p>		

**Table 4.1.2-1c: Tested CA Configurations Selection Criteria**

Code	Selection	Comment
FR2_Exy		

## 4.1.3 NR interworking between NR FR1 and NR FR2 and between NR and LTE conformance test cases

Table 4.1.3-1: Applicability of RF EN-DC FR1 and FR2 conformance test cases, ref. TS 38.521-3 [3]

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
<b>6</b>	<b>Transmitter Characteristics</b>					
<b>6.2</b>	<b>Transmitter power</b>					
<b>6.2B</b>	<b>Transmitter power for DC</b>					
<b>6.2B.1</b>	<b>UE Maximum Output Power for EN-DC</b>					
6.2B.1.1	UE Maximum Output Power for Intra-Band Contiguous EN-DC	Rel-15	C01	UEs supporting Intra-Band Contiguous EN-DC	D01	NOTE 1
6.2B.1.2	UE Maximum Output Power for Intra-Band Non-Contiguous EN-DC	Rel-15	C02	UEs supporting Intra-Band non-contiguous EN-DC within FR1	D01	NOTE 1
6.2B.1.3	UE Maximum Output Power for Inter-Band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-Band EN-DC within FR1	D01	
<b>6.2B.1.4</b>	<b>UE Maximum Output Power for Inter-Band EN-DC including FR2</b>					
6.2B.1.4.1	UE Maximum Output Power for Inter-Band EN-DC including FR2 - EIRP and TRP	Rel-15	C04	UEs supporting Inter-Band EN-DC including FR2	D02	NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.2.1.1 and skip TC 6.2B.1.4.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.1.4.2	UE Maximum Output Power for Inter-Band EN-DC including FR2 - Spherical Coverage	Rel-15	C04	UEs supporting Inter-Band EN-DC including FR2	D02	NOTE 1 NOTE 3
<b>6.2B.1.4_1</b>	<b>UE Maximum Output Power for Inter-Band EN-DC including FR2 (&gt;2 CCs)</b>					
<b>6.2B.1.4_1.1</b>	<b>UE Maximum Output Power for Inter-Band EN-DC including FR2 (3 CCs)</b>					

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.2B.1.4_1.1.1	UE Maximum Output Power for Inter-Band EN-DC including FR2 (3 CCs) - EIRP and TRP	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.2A.1.1.1 and skip TC 6.2B.1.4_1.1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.1.4_1.1.2	UE Maximum Output Power for Inter-Band EN-DC including FR2 (3 CCs) - Spherical Coverage	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
<b>6.2B.1.4_1.2</b>	<b>UE Maximum Output Power for Inter-Band EN-DC including FR2 (4 CCs)</b>					
6.2B.1.4_1.2.1	UE Maximum Output Power for Inter-Band EN-DC including FR2 (4 CCs) - EIRP and TRP	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.2A.1.1.2 and skip TC 6.2B.1.4_1.2.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.1.4_1.2.2	UE Maximum Output Power for Inter-Band EN-DC including FR2 (4 CCs) - Spherical Coverage	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
<b>6.2B.1.4_1.3</b>	<b>UE Maximum Output Power for Inter-Band EN-DC including FR2 (5 CCs)</b>					
6.2B.1.4_1.3.1	UE Maximum Output Power for Inter-Band EN-DC including FR2 (5 CCs) - EIRP and TRP	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.2A.1.1.3 and skip TC 6.2B.1.4_1.3.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.1.4_1.3.2	UE Maximum Output Power for Inter-Band EN-DC including FR2 (5 CCs) - Spherical Coverage	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
<b>6.2B.2</b>	<b>UE Maximum Output Power reduction for EN-DC</b>					
6.2B.2.1	UE Maximum Output Power reduction for Intra-Band Contiguous EN-DC	Rel-15	C01	UEs supporting Intra-Band Contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.2.2 and skip TC 6.2B.2.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.2.2	UE Maximum Output Power reduction for Intra-Band Non-Contiguous EN-DC	Rel-15	C02	UEs supporting Intra-Band non-contiguous EN-DC within FR1	D01	
6.2B.2.3	UE Maximum Output Power reduction for Inter-Band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-Band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 6.2.2 and skip TC 6.2B.2.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.2.4	UE Maximum Output Power reduction for Inter-Band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-Band EN-DC including FR2	D02	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.2.2 and skip TC 6.2B.2.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.2B.3</b>	<b>UE additional maximum output power reduction for EN-DC</b>					
6.2B.3.1	UE Additional Maximum Output Power reduction for Intra-band contiguous EN-DC	Rel-15	C01	UEs supporting Intra-Band Contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.2.3 and skip TC 6.2B.3.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.3.2	UE Additional Maximum Output Power reduction for Intra-Band Non-Contiguous EN-DC	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 6.2.3 and skip TC 6.2B.3.2 if UE

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						supports SA. E-UTRA is tested standalone using TS 36.521-1



Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.2B.3.3	UE additional Maximum Output power reduction for inter-band EN-DC within FR1	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 6.2.3 and skip TC 6.2B.3.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.2B.3.4	UE Additional Maximum Output Power reduction for Inter-Band EN-DC including FR2	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.2.3 and skip TC 6.2B.3.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.2B.4</b>	<b>Configured output power for EN-DC</b>					
<b>6.2B.4.1</b>	<b>Configured output power level for EN-DC</b>					
6.2B.4.1.1	Configured Output Power Level for Intra-Band Contiguous EN-DC	Rel-15	C01	UEs supporting Intra-Band Contiguous EN-DC	D01	NOTE 1
6.2B.4.1.2	Configured Output Power for Intra-Band Non-Contiguous EN-DC	Rel-15	C02	UEs supporting Intra-Band Non-Contiguous EN-DC	D01	NOTE 1
6.2B.4.1.3	Configured Output Power for Inter-Band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-Band EN-DC within FR1	D01	NOTE 1
<b>6.3</b>	<b>Output power dynamics</b>					
<b>6.3B</b>	<b>Output power dynamics for EN-DC</b>					
<b>6.3B.1</b>	<b>Minimum Output Power for EN-DC</b>					
6.3B.1.1	Minimum Output power for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.3.1 and skip TC 6.3B.1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.1.2	Minimum output power for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.3.1 and skip TC 6.3B.1.2 if UE supports SA. E-UTRA

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.3B.1.3	Minimum output power for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 6.3.1 and skip 6.3B.1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.1.4	Minimum Output Power for EN-DC Interband including FR2	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.3.1 and skip TC 6.3B.1.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.3B.2</b>	<b>Transmit OFF Power for EN-DC</b>					
<b>6.3B.2.4_1</b>	<b>Transmit OFF Power for inter-band EN-DC including FR2 (&gt;2 CCs)</b>					
6.3B.2.4_1.1	Transmit OFF Power for inter-band EN-DC including FR2 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.3A.2.1 and skip TC 6.3B.2.4_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.2.4_1.2	Transmit OFF Power for inter-band EN-DC including FR2 (4 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.3A.2.2 and skip TC 6.3B.2.4_1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.2.4_1.3	Transmit OFF Power for inter-band EN-DC including FR2 (5 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						TC 6.3A.2.3 and skip TC 6.3B.2.4_1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
<b>6.3B.3</b>	<b>Tx ON/OFF time mask for EN-DC</b>					
6.3B.3.1	Tx ON/OFF time mask for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.3.3.2 and skip TC 6.3B.3.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.3.2	Tx ON/OFF time mask for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.3.3.2 and skip TC 6.3B.3.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.3.3	Tx ON/OFF time mask for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 6.3.3.2 and skip TC 6.3B.3.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.3.4	Tx ON/OFF time mask for inter-band EN-DC including FR2	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
<b>6.3B.4</b>	<b>PRACH Time Mask</b>					
6.3B.4.1	PRACH time mask for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.3.3.4 and skip TC 6.3B.4.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.4.2	PRACH Time Mask for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.3.3.4 and skip TC 6.3B.4.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.3B.4.3	PRACH Time Mask for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC	D01	NOTE 5

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
				within FR1		Execute TS 38.521-1 TC 6.3.3.4 and skip TC 6.3B.4.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
<b>6.4</b>	<b>Transmit signal quality</b>					
<b>6.4B</b>	<b>Transmit Signal Quality for EN-DC</b>					
<b>6.4B.1</b>	<b>Frequency Error for EN-DC</b>					
6.4B.1.1	Frequency Error for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting Intra-Band Contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.1 and skip TC 6.4B.1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.1.2	Frequency Error for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	
6.4B.1.3	Frequency error for Inter-band EN-DC within FR1	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 6.4.1 and skip TC 6.4B.1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.1.4	Frequency Error for inter-band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-Band EN-DC including FR2	D02	NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.4.1 and skip TC 6.4B.1.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.4B.1.4_1</b>	<b>Frequency Error for inter-band EN-DC including FR2 (&gt;2 CCs)</b>					
6.4B.1.4_1.1	Frequency Error for inter-band EN-DC including FR2 (3 CCs)	Rel-15	C04	UEs supporting Inter-Band EN-DC including FR2	D02	NOTE 1 NOTE 3 NOTE 5
6.4B.1.4_1.2	Frequency Error for inter-band EN-DC including FR2 (4 CCs)	Rel-15	C04	UEs supporting Inter-Band EN-DC including FR2	D02	NOTE 1 NOTE 3 NOTE 5
6.4B.1.4_1.3	Frequency Error for inter-band EN-DC including FR2 (5 CCs)	Rel-15	C04	UEs supporting Inter-Band EN-DC including FR2	D02	NOTE 1 NOTE 3 NOTE 5
<b>6.4B.2</b>	<b>Transmit Modulation Quality EN-DC</b>					

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
<b>6.4B.2.1</b>	<b>Transmit Modulation Quality for intra-band contiguous EN-DC</b>					
6.4B.2.1.1	Error Vector Magnitude for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.1 and skip TC 6.4B.2.1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.2.1.2	Carrier Leakage for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.2 and skip TC 6.4B.2.1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.2.1.3	In-band Emissions for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	
6.4B.2.1.4	EVM Equalizer Flatness for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.4 and skip TC 6.4B.2.1.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.4B.2.2</b>	<b>Transmit Modulation Quality for intra-band non-contiguous EN-DC</b>					
6.4B.2.2.1	Error Vector Magnitude for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.1 and skip TC 6.4B.2.2.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.2.2.2	Carrier Leakage for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.2 and skip TC 6.4B.2.2.2 if UE supports SA. E-UTRA is tested standalone





Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.4B.2.2.3	In-band Emissions for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.3 and skip TC 6.4B.2.2.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.2.2.4	EVM Equalizer Flatness for intra-band non contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.4 and skip TC 6.4B.2.2.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.4B.2.3</b>	<b>Transmit Modulation Quality for inter-band EN-DC within FR1</b>					
6.4B.2.3.1	Error Vector Magnitude for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.1 and skip TC 6.4B.2.3.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.2.3.2	Carrier Leakage for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.2 and skip TC 6.4B.2.3.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.2.3.3	In-band Emissions for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.3 and skip TC 6.4B.2.3.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.4B.2.3.4	EVM Equalizer Flatness for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 6.4.2.4 and skip TC 6.4B.2.3.4 if UE

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
<b>6.4B.2.4</b>	<b>Transmit Modulation Quality for inter-band EN-DC including FR2</b>					
6.4B.2.4.1	Error Vector Magnitude for inter-band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 5 Execute TS 38.521-2 6.4.2.1 and skip 6.4B.2.4.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1. NOTE 1 NOTE 3
6.4B.2.4.2	Carrier Leakage for inter-band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 5 Execute TS 38.521-2 6.4.2.2 and skip 6.4B.2.4.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1. NOTE 1 NOTE 3
6.4B.2.4.3	In-band Emissions for inter-band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 5 Execute TS 38.521-2 6.4.2.3 and skip 6.4B.2.4.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1. NOTE 1 NOTE 3
6.4B.2.4.4	EVM Equalizer Flatness for inter-band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 5 Execute TS 38.521-2 6.4.2.4 and skip 6.4B.2.4.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1. NOTE 1 NOTE 3
<b>6.5B</b>	<b>Output RF spectrum emissions for EN-DC</b>					
<b>6.5B.1</b>	<b>Occupied bandwidth for EN-DC</b>					

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5B.1.1	Occupied bandwidth for Intra-Band Contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 1
6.5B.1.2	Occupied bandwidth for Intra-Band Non-Contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 1
6.5B.1.3	Occupied bandwidth for Inter-Band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 6.5.1 and skip 6.5B.1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.1.4	Occupied bandwidth for Inter-Band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 5 Execute TS 38.521-2 6.5.1 and skip 6.5B.1.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1. NOTE 1 NOTE 3
<b>6.5B.1.4_1</b>	<b>Occupied bandwidth for inter-band EN-DC including FR2 (&gt;2 CCs)</b>					
6.5B.1.4_1.1	Occupied bandwidth for inter-band EN-DC including FR2 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.1.1 and skip TC 6.5B.1.4_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.1.4_1.2	Occupied bandwidth for inter-band EN-DC including FR2 (4 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.1.2 and skip TC 6.5B.1.4_1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5B.1.4_1.3	Occupied bandwidth for inter-band EN-DC including FR2 (5 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.1.3 and skip TC 6.5B.1.4_1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.2</b>	<b>Out of Band emissions for EN-DC</b>					
<b>6.5B.2.1</b>	<b>Out of Band Emissions for intra-band contiguous EN-DC</b>					
6.5B.2.1.1	Spectrum emissions mask for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.5.2.2 and skip TC 6.5B.2.1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.2.1.2	Additional spectrum emissions mask for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.5.2.3 and skip TC 6.5B.2.1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.2.1.3	Adjacent channel leakage ratio for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.5.2.4.1 and skip TC 6.5B.2.1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.2.2</b>	<b>Out-of-band emissions for Intra-band non-contiguous EN-DC</b>					
6.5B.2.2.1	Spectrum emissions mask for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 6.5.2.2 and skip TC 6.5B.2.2.1 if UE

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5B.2.2.3	Adjacent channel leakage ratio for intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 6.5.2.4.1 and skip TC 6.5B.2.2.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.2.3</b>	<b>Out-of-band emissions for Inter-band EN-DC within FR1</b>					
6.5B.2.3.1	Spectrum emissions mask for Inter-band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 6.5.2.2 and skip 6.5B.2.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.2.3.2	Additional Spectrum emissions mask for Inter-band EN-DC within FR1	Rel-15	FFS	FFS	FFS	NOTE 1
6.5B.2.3.3	Adjacent channel leakage ratio for inter-band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 6.5.2.4.1 and skip 6.5B.2.3.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.2.4</b>	<b>Out-of-band emissions for Inter-band EN-DC including FR2</b>					
6.5B.2.4.1	Spectrum emissions mask for Inter-band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5.2.1 and skip TC 6.5B.2.4.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.2.4.1_1</b>	<b>Spectrum emissions mask for Inter-band EN-DC including FR2 (&gt;2 CCs)</b>					
6.5B.2.4.1_1.1	Spectrum emissions mask for Inter-band EN-DC including FR2 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3



Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						NOTE 5 Execute TS 38.521-2 TC 6.5A.2.1.1 and skip TC 6.5B.2.4.1_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5B.2.4.1_1.2	Spectrum emissions mask for Inter-band EN-DC including FR2 (4 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.2.1.2 and skip TC 6.5B.2.4.1_1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.2.4.1_1.3	Spectrum emissions mask for Inter-band EN-DC including FR2 (5 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.2.1.3 and skip TC 6.5B.2.4.1_1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.2.4.3	Adjacent channel leakage ratio for Inter-band EN-DC including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 5 Execute TS 38.521-2 6.5.2.3 and skip 6.5B.1.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1. NOTE 1 NOTE 3
<b>6.5B.2.4.3_1</b>	<b>Adjacent channel leakage ratio for Inter-band EN-DC including FR2 (&gt;2 CCs)</b>					
6.5B.2.4.3_1.1	Adjacent channel leakage ratio for Inter-band EN-DC including FR2 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.2.2.1 and skip TC 6.5B.2.4.3_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5B.2.4.3_1.2	Adjacent channel leakage ratio for Inter-band EN-DC including FR2 (4 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.2.2.2 and skip TC 6.5B.2.4.3_1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.2.4.3_1.3	Adjacent channel leakage ratio for Inter-band EN-DC including FR2 (5 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.2.2.3 and skip TC 6.5B.2.4.3_1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.3</b>	<b>Spurious emissions for EN-DC</b>					
<b>6.5B.3.1</b>	<b>Spurious Emissions for intra-band contiguous EN-DC</b>					
6.5B.3.1.1	General spurious emissions for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.5.3.1 and skip TC 6.5B.3.1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.3.1.2	Spurious emission band UE co-existence for intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 6.5.3.2 and skip TC 6.5B.3.1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.3.2</b>	<b>Spurious Emissions for intra-band non-contiguous EN-DC</b>					
6.5B.3.2.1	General spurious emissions for intra-band non-	Rel-15	C02	UEs supporting intra-band non-	D01	NOTE 5

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
	contiguous EN-DC			contiguous EN-DC		Execute TS 38.521-1 TC 6.5.3.1 and skip TC 6.5B.3.2.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5B.3.2.2	Spurious emission band UE co-existence for intra-band non-contiguous EN-DC	Rel-15	FFS	FFS	FFS	NOTE 1
<b>6.5B.3.3</b>	<b>Spurious emissions for Inter-band EN-DC within FR1</b>					
6.5B.3.3.1	General spurious emissions for Inter-band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 6.5.3.1 and skip 6.5B.3.3.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.3.3.2	Spurious emission band UE co-existence for Inter-band within FR1	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	
<b>6.5B.3.4</b>	<b>Spurious emissions for Inter-band including FR2</b>					
6.5B.3.4.1	General Spurious Emissions for Inter-band including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5.3.1 and skip TC 6.5B.3.4.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.3.4.1_1</b>	<b>General Spurious Emissions for Inter-band including FR2 (&gt;2 CCs)</b>					
6.5B.3.4.1_1.1	General Spurious Emissions for Inter-band including FR2 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.3.1.1 and skip TC 6.5B.3.4.1_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.3.4.1_1.2	General Spurious Emissions for Inter-band including FR2 (4 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.3.1.2 and

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						skip TC 6.5B.3.4.1_1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
6.5B.3.4.1_1.3	General Spurious Emissions for Inter-band including FR2 (5 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 6.5A.3.1.3 and skip TC 6.5B.3.4.1_1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
6.5B.3.4.2	Spurious emission band UE co-existence for Inter-band including FR2	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 1 NOTE 3
<b>6.5B.4</b>	<b>Additional Spurious Emissions</b>					
6.5B.4.1	Additional Spurious Emissions for Intra-band contiguous EN-DC	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	
6.5B.4.2	Additional Spurious Emissions for Intra-band non-contiguous EN-DC	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 1
6.5B.4.3	Additional Spurious Emissions for Inter-band EN-DC	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 6.5.4 and skip TC 6.5B.4.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>6.5B.5</b>	<b>Transmit Intermodulation</b>					
6.5B.5.3	Transmit Intermodulation for Inter-band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	
<b>7</b>	<b>Receiver Characteristics</b>					
<b>7.1</b>	<b>General</b>					
<b>7.2</b>	<b>Diversity characteristics</b>					
<b>7.3</b>	<b>Reference sensitivity</b>					
<b>7.3A</b>	<b>Reference sensitivity for CA without EN-DC</b>					
<b>7.3A.1</b>	<b>General</b>					
<b>7.3B</b>	<b>Reference sensitivity level for DC</b>					
<b>7.3B.2</b>	<b>Reference Sensitivity for EN-DC</b>					
7.3B.2.1	Reference sensitivity for intra-band contiguous EN-DC (2 CCs)	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 7.3.2 and skip TC 7.3B.2.1 if UE supports SA. E-UTRA

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						is tested standalone using TS 36.521-1



Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
7.3B.2.2	Reference sensitivity for Intra-band non-contiguous EN-DC (2 CCs)	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 7.3.2 and skip TC 7.3B.2.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.3B.2.3	Reference sensitivity for Inter-band EN-DC within FR1	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	
<b>7.3B.2.3_1</b>	<b>Reference sensitivity for EN-DC within FR1 (&gt;2 CCs)</b>					
7.3B.2.3_1.1	Reference sensitivity for EN-DC within FR1 (3 CCs)	Rel-15	FFS	FFS	FFS	
7.3B.2.4	Reference sensitivity for Inter-band EN-DC including FR2 (2 CCs)	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-2 7.3.2 and skip 7.3B.2.4.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1 NOTE 3
<b>7.3B.2.4_1</b>	<b>Reference sensitivity for Inter-band EN-DC including FR2 (&gt;2 CCs)</b>					
7.3B.2.4_1.1	Reference sensitivity for Inter-band EN-DC including FR2 (3 CCs)	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 3 NOTE 5 Execute TS 38.521-2 7.3.2 and skip 7.3B.2.4_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.4</b>	<b>Maximum Input Level</b>					
<b>7.4B</b>	<b>Maximum Input Level for EN-DC</b>					
7.4B.1	Maximum Input Level for Intra-Band Contiguous EN-DC (2 CCs)	Rel-15	C01	UEs supporting Intra-Band Contiguous EN-DC	D01	
7.4B.2	Maximum Input Level for Intra-Band Non-Contiguous EN-DC (2 CCs)	Rel-15	C02	UEs supporting Intra-Band Non-Contiguous EN-DC	D01	
7.4B.3	Maximum Input Level for Inter-band EN-DC within FR1	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 7.4 and skip 7.4B.3 if UE supports SA. E-

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
7.4B.4	Maximum Input Level for inter-band EN-DC including FR2 (2 CCs)	Rel-15	C04	UEs supporting Inter-band including FR2	D02	NOTE 1 NOTE 3
7.5B.1	Adjacent Channel Selectivity for intra-band contiguous EN-DC (2 CCs)	Rel-15	C01	UEs supporting intra-band contiguous EN-DC	D01	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.5 and skip TC 7.5B.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.5B.2	Adjacent Channel Selectivity for intra-band non-contiguous EN-DC (2 CCs)	Rel-15	C02	UEs supporting intra-band non-contiguous EN-DC	D01	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.5 and skip TC 7.5B.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.5B.3	Adjacent Channel Selectivity for inter-band EN-DC within FR1 (2 CCs)	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	Execute TS 38.521-1 7.5 and skip 7.5B.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1 NOTE 5 Execute TS 38.521-1 TC 7.5 and skip TC 7.5B.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.5B.4.1	Adjacent Channel Selectivity for inter-band EN-DC including FR2 (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 7.5 and skip TC 7.5B.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.5B.4_1</b>	<b>Adjacent Channel Selectivity for inter-band EN-</b>					

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
	DC including FR2 (>2 CCs)					

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
7.5B.4_1.1	Adjacent Channel Selectivity for inter-band EN-DC including FR2 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 7.5A.1 and skip TC 7.5B.4_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.5B.4_1.2	Adjacent Channel Selectivity for inter-band EN-DC including FR2 (4 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 7.5A.2 and skip TC 7.5B.4_1.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.5B.4_1.3	Adjacent Channel Selectivity for inter-band EN-DC including FR2 (5 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 7.5A.3 and skip TC 7.5B.4_1.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.5B.4_1.4	Adjacent Channel Selectivity for inter-band EN-DC including FR2 (6 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 7.5A.4 and skip TC 7.5B.4_1.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.6A	Blocking Characteristics for CA	Rel-15	FFS	FFS	FFS	NOTE 1
<b>7.6B</b>	<b>Blocking Characteristics for EN-DC in FR1</b>					
<b>7.6B.1</b>	<b>General</b>					
<b>7.6B.2</b>	<b>Inband blocking for EN-DC within FR1</b>					

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
7.6B.2.1	Inband blocking for intra-band contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.6.2 and skip TC 7.6B.2.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.6B.2.2	Inband blocking for intra-band non-contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.6.2 and skip TC 7.6B.2.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.6B.2.3	Inband blocking for inter-band EN-DC within FR1 (2 CCs)	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 7.6.2 and skip 7.6B.2.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.6B.2.4	Inband blocking for inter-band EN-DC including FR2 (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3 NOTE 5 Execute TS 38.521-2 TC 7.6.2 and skip TC 7.6B.2.4 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.6B.3</b>	<b>Out-of-band blocking for EN-DC in FR1</b>					
7.6B.3.1	Out-of-band blocking for intra-band contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.6.3 and skip TC 7.6B.3.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
7.6B.3.2	Out-of-band blocking for intra-band non-contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.6.3 and skip TC 7.6B.3.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.6B.3.3	Out-of-band blocking for inter-band EN-DC within FR1 (2 CCs)	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	
<b>7.6B.4</b>	<b>Narrow band blocking for EN-DC in FR1</b>					
7.6B.4.1	Narrow band blocking for intra-band contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.6.4 and skip TC 7.6B.4.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.6B.4.2	Narrow band blocking for intra-band non-contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.6.4 and skip TC 7.6B.4.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.6B.4.3	Narrow band blocking for inter-band EN-DC within FR1 (2 CCs)	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 7.6.4 and skip 7.6B.4.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.7</b>	<b>Spurious Response</b>					
<b>7.7B</b>	<b>Spurious Response for EN-DC in FR1</b>					
7.7B.1	Spurious Response for intra-band contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1
7.7B.2	Spurious Response for intra-band non-contiguous EN-DC (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
						Execute TS 38.521-1 TC 7.7 and skip TC 7.7B.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1



Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
7.7B.3	Spurious Response for inter-band EN-DC within FR1 (2 CCs)	Rel-15	C03	UEs supporting Inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 7.7 and skip 7.7B.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.8</b>	<b>Intermodulation Characteristics</b>					
<b>7.8B</b>	<b>Intermodulation Characteristics for EN-DC in FR1</b>					
<b>7.8B.1</b>	<b>General</b>					
<b>7.8B.2</b>	<b>Wideband Intermodulation</b>					
7.8B.2.1	Wideband Intermodulation for intra-band contiguous EN-DC in FR1	Rel-15	C01	UEs supporting Intra-Band Contiguous EN-DC	D01	NOTE 1
7.8B.2.2	Wideband Intermodulation for intra-band non-contiguous EN-DC in FR1	Rel-15	C02	UEs supporting Intra-Band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 7.8.2 and skip 7.8B.2.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.8B.2.3	Wideband Intermodulation for inter-band EN-DC in FR1 (2 CCs)	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 7.8.2 and skip TC 7.8B.2.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.8B.2.3_1</b>	<b>Wideband Intermodulation for inter-band EN-DC within FR1 (&gt;2 CCs)</b>					
7.8B.2.3_1.1	Wideband Intermodulation for EN-DC within FR1 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 5 Execute TS 38.521-1 TC 7.8A.2.1 and skip TC 7.8B.2.3_1.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.9</b>	<b>Spurious Emissions</b>					
<b>7.9B</b>	<b>Spurious Emissions for EN-DC in FR1</b>					
7.9B.1	Spurious Emissions for intra-band contiguous EN-	Rel-15	C01	UEs supporting Intra-Band	D01	NOTE 5

Clause	TC Title	Release	Applicability		Tested Bands/CA-Configurations Selection	Additional Information
			Condition	Comment		
	DC in FR1(2 CCs)			Contiguous EN-DC		Execute TS 38.521-1 TC 7.9 and skip TC 7.9B.1 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.9B.2	Spurious Emissions for intra-band non-contiguous EN-DC in FR1(2 CCs)	Rel-15	C02	UEs supporting Intra-Band non-contiguous EN-DC	D01	NOTE 5 Execute TS 38.521-1 TC 7.9 and skip TC 7.9B.2 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
7.9B.3	Spurious Emissions for inter-band EN-DC within FR1 (2 CCs)	Rel-15	C03	UEs supporting inter-band EN-DC within FR1	D01	NOTE 5 Execute TS 38.521-1 TC 7.9 and skip TC 7.9B.3 if UE supports SA. E-UTRA is tested standalone using TS 36.521-1
<b>7.9B.3_1</b>	<b>Spurious Emissions for inter-band EN-DC within FR1 (&gt;2 CCs)</b>					
7.9B.4	Spurious Emissions for inter-band EN-DC including FR2 (2 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
<b>7.9B.4_1</b>	<b>Spurious Emissions for inter-band EN-DC including FR2 (&gt;2 CCs)</b>					
7.9B.4_1.1	Spurious Emissions for inter-band EN-DC including FR2 (3 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
7.9B.4_1.2	Spurious Emissions for inter-band EN-DC including FR2 (4 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
7.9B.4_1.3	Spurious Emissions for inter-band EN-DC including FR2 (5 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
7.9B.4_1.4	Spurious Emissions for inter-band EN-DC including FR2 (6 CCs)	Rel-15	FFS	FFS	FFS	NOTE 1 NOTE 3
NOTE 1: The test case is incomplete.						
NOTE 2: The test case applicability is set to N/A until the related testability issues are resolved.						
NOTE 3: For conformance testing involving FR2 test cases, the UE under test shall disable UL Tx diversity schemes.						
NOTE 4: All Power Class 3 UE supported bands needs to be tested to ensure the multiband relaxation declaration is compliant.						
NOTE 5: Test only one EN-DC combination per 5G NR band as LTE anchor agnostic approach is applied.						

**Table 4.1.3-1a: Applicability of RF EN-DC conformance test cases Conditions**

C01	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/2 AND A.4.1-4/1 THEN R ELSE N/A
C02	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/2 AND A.4.1-4/2 THEN R ELSE N/A
C03	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/2 AND A.4.1-4/3 THEN R ELSE N/A
C04	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/2 AND A.4.1-4/4 THEN R ELSE N/A
C05	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/2 AND (A.4.1-4/3 OR A.4.1-4/4) THEN R ELSE N/A
C06	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/2 AND (A.4.1-4/1 OR A.4.1-4/2 OR A.4.1-4/3 OR A.4.1-4/4) THEN R ELSE N/A
NOTE 1: The ICS proforma are defined in TS 38.508-2 [8] unless otherwise stated.	

**Table 4.1.3-1b: Tested Bands Selection Criteria for RF EN-DC conformance test cases**

Code	Selection	Comment
	A.4.3.1-1 OR A.4.3.1-2	All supported FR1 Bands
	A.4.3.1-3	All supported FR2 Bands
	A.4.3.1-1 OR A.4.3.1-2 OR A.4.3.1-3	All supported NR Bands
<p>NOTE 1: Band Selection is based on set theory. For each feature, item number shall correspond to the Band number. The result is the set of bands for which the test shall be conducted. The following operators are used:</p> <p>AND: Set intersection (<math>\cap</math>). {1,2} AND {2,3} = {2}</p> <p>OR: Set union (<math>\cup</math>). {1,2} OR {2,3} = {1,2,3}</p> <p>NOT: Set complement (<math>\setminus</math>), full set being all bands. NOT{1} = {2 ...256}</p> <p>Also note that this is set without repetitions so {1} AND {1} = {1}</p> <p>The following basic sets are used:</p> <p>{1,2}: Explicitly given band set</p> <p>10MHz: All bands supporting 10 MHz</p> <p>The following sets derived from pro-forma tables are also used:</p> <p>TBD</p>		

**Table 4.1.3-1c: Tested CA Configurations Selection Criteria for RF EN-DC conformance test cases**

Code	Selection	Comment
Exy		

## 4.1.4 Performance conformance test cases

Table 4.1.4-1: Applicability of performance test cases, ref. TS 38.521-4 [4]

Clause	TC Title	Release	Applicability		Tested Bands Selection	Additional Information
			Condition	Comment		
<b>5</b>	<b>Demodulation performance requirements (Conducted requirements)</b>					
<b>5.2</b>	<b>PDSCH demodulation requirements</b>					
5.2.2.1.1_1	2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01, Perf_D03	Test case execution not necessary if 5.2.3.1.1_1 is executed
5.2.2.1.1_2	2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA	Rel-15	Perf_C01a	UEs supporting 5GS FDD FR1 and Enhanced Receiver Type 1	Perf_D01	
5.2.2.1.2_1	2Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 5.2.3.1.2_1 is executed
5.2.2.1.3_1	2Rx FDD FR1 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01, Perf_D03	NOTE 1
5.2.2.1.4_1	2Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x2 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C05	UEs supporting 5GS FDD FR1 and additional DMRS for coexistence with LTE CRS	Perf_D01	Test case execution not necessary if 5.2.3.1.4_1 is executed
5.2.2.2.1_1	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D02, Perf_D03	Test case execution not necessary if 5.2.3.2.1_1 is executed
5.2.2.2.1_2	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA	Rel-15	Perf_C02a	UEs supporting 5GS TDD FR1 and Enhanced Receiver Type 1	Perf_D03	
5.2.2.2.2_1	2Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 5.2.3.2.2_1 is executed
5.2.2.2.3_1	2Rx TDD FR1 PDSCH mapping Type B performance -- 2x2 MIMO with baseline receiver for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1
5.2.3.1.1_1	4Rx FDD FR1 PDSCH mapping Type A performance - 2x4 MIMO baseline receiver for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01, Perf_D02	

Clause	TC Title	Release	Applicability		Tested Bands Selection	Additional Information
			Condition	Comment		
5.2.3.1.1_2	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO baseline receiver for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01, Perf_D02	
5.2.3.1.1_4	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA	Rel-15	Perf_C03a	UEs supporting 5GS FDD FR1 and 4Rx antenna ports and Enhanced Receiver Type 1	Perf_D01	
5.2.3.1.2_1	4Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 4x4 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01,	NOTE 1
5.2.3.1.3_1	4Rx FDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01, Perf_D02	NOTE 1
5.2.3.1.4_1	4Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x4 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C03c	UEs supporting 5GS FDD FR1 and 4Rx antenna ports and LTE-NR coexistence	Perf_D01	
5.2.3.2.1_1	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D02, Perf_D03	
5.2.3.2.1_2	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D03	
5.2.3.2.1_4	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA	Rel-15	Perf_C06a	UEs supporting 5GS TDD FR1 and Enhanced Receiver Type 1 and 4Rx antenna ports	Perf_D03	
5.2.3.2.2_1	4Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x4 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D02, Perf_D03	NOTE 1
5.2.3.2.3_1	4Rx TDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D02, Perf_D03	NOTE 1
5.3.2.1.1	2Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 5.3.3.1.1 is executed
5.3.2.1.2	2Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 5.3.3.1.2 is executed
5.3.2.2.1	2Rx TDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 5.3.3.2.1 is executed
5.3.2.2.2	2Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 5.3.3.2.2 is executed
5.3.3.1.1	4Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01	
5.3.3.1.2	4Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01	
5.3.3.2.1	4Rx TDD FR1 PDCCH 1 Tx antenna performance for	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and	Perf_D03	

Clause	TC Title	Release	Applicability		Tested Bands Selection	Additional Information
			Condition	Comment		
	both SA and NSA			4Rx antenna ports		

Clause	TC Title	Release	Applicability		Tested Bands Selection	Additional Information
			Condition	Comment		
5.3.3.2.2	4Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D03	
5.5.1	FR1 Sustained downlink data rate performance for single carrier	Rel-15	Perf_C07	UEs supporting 5GS FDD FR1 or TDD FR1 (SA)	Perf_D01 Perf_D02 Perf_D03	
<b>6</b>	<b>CSI reporting requirements</b>					
6.2.2.1.1.1	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 6.2.3.1.1.1 is executed
6.2.2.1.2.1	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 6.2.3.1.2.1 is executed
6.2.2.1.2.2	2Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 6.2.3.1.2.2 is executed
6.2.2.2.1.1	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 6.2.3.2.1.1 is executed
6.2.2.2.2.1	2Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 6.2.3.2.2.1 is executed
6.2.2.2.2.2	2Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 6.2.3.2.2.2 is executed
6.2.3.1.1.1	4Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01	NOTE 1
6.2.3.1.2.1	4Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01	
6.2.3.1.2.2	4Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C03	UEs supporting 5GS FDD FR1 and 4Rx antenna ports	Perf_D01	
6.2.3.2.1.1	4Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D03	NOTE 1
6.2.3.2.2.1	4Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D03	
6.2.3.2.2.2	4Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	Rel-15	Perf_C06	UEs supporting 5GS TDD FR1 and 4Rx antenna ports	Perf_D03	
6.3.2.1.1	2Rx FDD FR1 Single PMI with 4Tx Type1 – SinglePanel codebook for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 6.3.3.1.1 is executed
6.3.2.1.2	2Rx FDD FR1 Single PMI with 8Tx Type1 – SinglePanel codebook for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 6.3.3.1.2 is executed

Clause	TC Title	Release	Applicability		Tested Bands Selection	Additional Information
			Condition	Comment		
6.3.2.2.1	2Rx TDD FR1 Single PMI with 4Tx Type1 - SinglePanel codebook for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 6.3.3.2.1 is executed
6.3.2.2.2	2Rx TDD FR1 Single PMI with 8Tx Type1 - SinglePanel codebook for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 6.3.3.2.2 is executed
6.3.3.1.1	4Rx FDD FR1 Single PMI with 4Tx Type1 -- SinglePanel codebook for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1
6.3.3.1.2	4Rx FDD FR1 Single PMI with 8Tx Type1 -- SinglePanel codebook for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1
6.3.3.2.1	4Rx TDD FR1 Single PMI with 4Tx Type1 -- SinglePanel codebook for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1
6.3.3.2.2	4Rx TDD FR1 Single PMI with 8Tx Type1 -- SinglePanel codebook for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1
6.4.2.1_1	2Rx FDD FR1 RI reporting for both SA and NSA	Rel-15	Perf_C01	UEs supporting 5GS FDD FR1	Perf_D01	Test case execution not necessary if 6.4.3.1_1 is executed NOTE 1
6.4.2.2_1	2Rx TDD FR1 RI reporting for both SA and NSA	Rel-15	Perf_C02	UEs supporting 5GS TDD FR1	Perf_D03	Test case execution not necessary if 6.4.3.2_1 is executed
6.4.3.2_1	4Rx TDD FR1 RI reporting for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1
<b>7</b>	<b>Demodulation performance requirements (Radiated requirements)</b>					
7.2.2.2.1_1	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for SA and NSA	FFS	FFS	FFS	FFS	NOTE 1 NOTE 3
7.2.2.2.1_2	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with enhanced type 1 receiver for SA and NSA	FFS	FFS	FFS	FFS	NOTE 1 NOTE 3
7.3.2.2.1	2Rx TDD FR2 PDCCH 1 Tx antenna performance for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1 NOTE 3
7.3.2.2.2	2Rx TDD FR2 PDCCH 2 Tx antenna performance for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1 NOTE 3
<b>8</b>	<b>CSI reporting requirements (Radiated requirements)</b>					
8.3.2.2.1	2Rx TDD FR2 Single PMI with 2Tx Type1 -- SinglePanel codebook for both SA and NSA	FFS	FFS	FFS	FFS	NOTE 1
<b>9</b>	<b>Demodulation performance requirements for interworking (Radiated requirements)</b>					
9.4B.1.1	SDR test for sustained downlink data rate performance for EN-DC within FR1	Rel-15	Perf_C07a	UEs supporting 5GS FDD FR1 or TDD FR1 (NSA)	Perf_D01 Perf_D02 Perf_D03	



Clause	TC Title	Release	Applicability		Tested Bands Selection	Additional Information
			Condition	Comment		
<b>10</b>	<b>CSI reporting requirements for interworking</b>					
NOTE 1: The test case is incomplete.						
NOTE 2: Void.						
NOTE 3: For conformance testing involving FR2 test cases, the UE under test shall disable UL Tx diversity schemes.						

**Table 4.1.4-1a: Applicability of RF performance conformance test cases Conditions**

Perf_C01	IF A.4.1-1/1 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) THEN R ELSE N/A
Perf_C01a	IF A.4.1-1/1 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND A.4.3.9-1/1 THEN R ELSE N/A
Perf_C02	IF A.4.1-1/2 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) THEN R ELSE N/A
Perf_C02a	IF A.4.1-1/2 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND A.4.3.9-1/1 THEN R ELSE N/A
Perf_C03	IF A.4.1-1/1 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND 4.1.4-1c/1 THEN R ELSE N/A
Perf_C03a	IF A.4.1-1/1 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND A.4.3.9-1/1 AND 4.1.4-1c/1 THEN R ELSE N/A
Perf_C03c	IF A.4.1-1/1 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND A.4.3.2-1/20 AND 4.1.4-1c/1 THEN R ELSE N/A
Perf_C04	IF A.4.1-1/2 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) THEN R ELSE N/A
Perf_C04a	IF A.4.1-1/2 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND A.4.3.9-1/1 THEN R ELSE N/A
Perf_C05	IF A.4.1-1/1 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND A.4.3.2-1/20 THEN R ELSE N/A
Perf_C06	IF A.4.1-1/2 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND 4.1.4-1c/2 THEN R ELSE N/A
Perf_C06a	IF A.4.1-1/2 AND (A.4.1-3/1 OR A.4.1-3/2 OR A.4.1-3/3 OR A.4.1-3/5) AND A.4.3.9-1/1 AND 4.1.4-1c/2 THEN R ELSE N/A
Perf_C07	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/1 THEN R ELSE N/A
Perf_C07a	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/2 THEN R ELSE N/A
NOTE 1: The ICS proforma are defined in TS 38.508-2 [8] unless otherwise stated.	

**Table 4.1.4-1b: Tested Bands Selection Criteria for RF performance conformance test cases**

	Selection	Comment
Perf_D01	ANY( (A.4.3.1-1 OR A.4.3.1-2) AND 10MHz )	Any band within the set supporting 10 MHz UE Channel BW
Perf_D02	ANY( (A.4.3.1-1 OR A.4.3.1-2) AND 20MHz )	Any band within the set supporting 20 MHz UE Channel BW
D03	ANY( (A.4.3.1-1 OR A.4.3.1-2) AND 40MHz )	Any band within the set supporting 40 MHz UE Channel BW
<p>NOTE 1: Band Selection is based on set theory. For each feature, item number shall correspond to the Band number. The result is the set of bands for which the test shall be conducted. The following operators are used:</p> <p>AND: Set intersection (<math>\cap</math>). {1,2} AND {2,3} = {2}</p> <p>OR: Set union (<math>\cup</math>). {1,2} OR {2,3} = {1,2,3}</p> <p>NOT: Set complement (<math>\setminus</math>), full set being all bands. NOT{1} = {2 ...256}</p> <p>Also note that this is set without repetitions so {1} AND {1} = {1}</p> <p>The following basic sets are used:</p> <p>{1,2}: Explicitly given band set</p> <p>10MHz: All bands supporting 10 MHz</p> <p>The following derived sets are also used:</p> <p>ANY(): Arbitrarily select a band within set</p>		

**Table 4.1.4-1c: UE 4Rx derived capabilities**

Item	UE declared capabilities	Ref.	Release	Condition	Comments
1	Support of 4Rx antenna ports in at least one FDD frequency band	38.101-1, 7.2	Rel-15	NOT A.4.3.9-1/2 AND A.4.3.9-4/7 OR (A.4.3.9-4/1 OR A.4.3.9-4/2 OR A.4.3.9-4/3 OR A.4.3.9-4/66)	
2	Support of 4Rx antenna ports in at least one TDD frequency band	38.101-1, 7.2	Rel-15	NOT A.4.3.9-1/2 AND (A.4.3.9-4/38 OR A.4.3.9-4/41 OR A.4.3.9-4/77 OR A.4.3.9-4/78 OR A.4.3.9-4/79) OR (A.4.3.9-4/34, A.4.3.9-4/39 OR A.4.3.9-4/40 OR A.4.3.9-4/48 OR A.4.3.9-4/70)	

## 4.2 RRM conformance test cases

Table 4.2-1: Applicability of RRM EN-DC FR1 conformance test cases, ref. TS 38.533 [5]

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
<b>4.3</b>	<b>RRC_CONNECTED state mobility</b>					
<b>4.3.2</b>	<b>RRC connection mobility control</b>					
<b>4.3.2.2</b>	<b>Random access</b>					
4.3.2.2.1	Contention based random access test in FR1 for PSCell in EN-DC	FFS	FFS	FFS		
4.3.2.2.2	Non-contention based random access test in FR1 for PSCell in EN-DC	FFS	FFS	FFS	NOTE 1	
<b>4.4</b>	<b>Timing</b>					
<b>4.4.1</b>	<b>UE Transmit Timing</b>					
4.4.1.1	EN-DC FR1 UE transmit timing accuracy	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
<b>4.4.2</b>	<b>UE timer accuracy</b>					
<b>4.4.3</b>	<b>Timing Advance</b>					
4.4.3.1	EN-DC FR1 timing advance adjustment accuracy	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
<b>4.5</b>	<b>Signalling characteristics</b>					
<b>4.5.1</b>	<b>Radio link monitoring</b>					
4.5.1.1	EN-DC FR1 radio link monitoring out-of-sync test for PSCell configured with SSB-based RLM RS in non-DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.1.2	EN-DC FR1 radio link monitoring in-sync test for PSCell configured with SSB-based RLM RS in non-DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.1.3	EN-DC FR1 radio link monitoring out-of-sync test for PSCell configured with SSB-based RLM RS in DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.1.4	EN-DC FR1 radio link monitoring in-sync test for PSCell configured with SSB-based RLM RS in DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.1.5	EN-DC FR1 radio link monitoring out-of-sync test for PSCell configured with CSI-RS-based RLM RS in non-DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.1.6	EN-DC FR1 radio link monitoring in-sync test for PSCell configured with CSI-RS-based RLM RS in non-DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.1.7	EN-DC FR1 radio link monitoring out-of-sync test for PSCell configured with CSI-RS-based RLM RS in DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.1.8	EN-DC FR1 radio link monitoring in-sync test for PSCell configured with CSI-RS-based RLM RS in DRX mode	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
<b>4.5.2</b>	<b>Interruption</b>					

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
4.5.2.1	EN-DC FR1 interruptions at transitions between active and non-active during DRX in synchronous EN-DC	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.2.2	EN-DC FR1 interruptions at transitions between active and non-active during DRX in asynchronous EN-DC	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.5.2.3	EN-DC FR1 interruptions during measurements on deactivated NR SCC in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
4.5.2.4	EN-DC FR1 interruptions during measurements on deactivated NR SCC in asynchronous EN-DC	FFS	FFS	FFS	NOTE 1	
4.5.2.5	EN-DC FR1 interruptions during measurements on deactivated E-UTRAN SCC in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
4.5.2.6	EN-DC FR1 interruptions during measurements on deactivated E-UTRAN SCC in asynchronous EN-DC	FFS	FFS	FFS	NOTE 1	
<b>4.5.3</b>	<b>SCell activation and deactivation delay</b>					
4.5.3.1	EN-DC FR1 SCell activation and deactivation of known SCell in non-DRX for 160ms SCell measurement cycle	FFS	FFS	FFS	NOTE 1	
4.5.3.2	EN-DC FR1 SCell activation and deactivation of known SCell in non-DRX for 320ms SCell measurement cycle	FFS	FFS	FFS	NOTE 1	
4.5.3.3	EN-DC FR1 SCell activation and deactivation of unknown SCell in non-DRX	FFS	FFS	FFS	NOTE 1	
<b>4.5.4</b>	<b>UE UL carrier RRC reconfiguration delay</b>					
<b>4.5.5</b>	<b>Beam failure detection and link recovery procedures</b>					
4.5.5.4	EN-DC FR1 CSI-RS-based beam failure detection and link recovery in DRX	FFS	FFS	FFS	NOTE 1	
<b>4.5.6</b>	<b>Active BWP switch delay</b>					
<b>4.5.6.1</b>	<b>DCI-based and timer-based active BWP switch</b>					
4.5.6.1.1	EN-DC FR1 DCI-based DL active BWP switch in non-DRX in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
4.5.6.1.2	EN-DC FR1 DCI-based DL active BWP switch with SCell in non-DRX in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
<b>4.5.6.2</b>	<b>RRC-based active BWP switch</b>					
4.5.6.2.1	EN-DC FR1 RRC-based DL active BWP switch in non-DRX in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
<b>4.5.7</b>	<b>PSCell addition and release delay</b>					
<b>4.6</b>	<b>Measurement procedures</b>					
<b>4.6.1</b>	<b>Intra-frequency measurements</b>					
4.6.1.1	EN-DC FR1 event-triggered reporting without gap in non-DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.6.1.2	EN-DC FR1 event-triggered reporting without gap in DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.6.1.3	EN-DC FR1 event-triggered reporting with gap in non-	Rel-15	RE1_C001	UEs supporting EN-DC FR1		

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
	DRX					

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
4.6.1.4	EN-DC FR1 event-triggered reporting with gap in DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.6.1.5	EN-DC FR1 event-triggered reporting without gap in non-DRX with SSB time index detection	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.6.1.6	EN-DC FR1 event-triggered reporting with gap in non-DRX with SSB time index detection	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
<b>4.6.2</b>	<b>Inter-frequency measurements</b>					
4.6.2.1	EN-DC FR1-FR1 event-triggered reporting in non-DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.6.2.2	EN-DC FR1-FR1 event-triggered reporting in DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.6.2.5	EN-DC FR1-FR1 event-triggered reporting in non-DRX with SSB time index detection	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.6.2.6	EN-DC FR1-FR1 event-triggered reporting in DRX with SSB time index detection	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
<b>4.6.3</b>	<b>L1-RSRP for beam reporting</b>					
4.6.3.1	EN-DC FR1 SSB-based L1-RSRP measurement in non-DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1	NOTE 1	
4.6.3.2	EN-DC FR1 SSB-based L1-RSRP measurement in DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1	NOTE 1	
4.6.3.3	EN-DC FR1 CSI-RS-based L1-RSRP measurement in non-DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1	NOTE 1	
4.6.3.4	EN-DC FR1 CSI-RS-based L1-RSRP measurement in DRX	Rel-15	RE1_C001	UEs supporting EN-DC FR1	NOTE 1	
<b>4.7</b>	<b>Measurement performance requirements</b>					
<b>4.7.1</b>	<b>SS-RSRP</b>					
<b>4.7.1.1</b>	<b>Intra-frequency measurements</b>					
4.7.1.1.1	EN-DC FR1 SS-RSRP absolute measurement accuracy	Rel-15	RE1_C001	UEs supporting EN-DC FR1	NOTE 1	
4.7.1.1.2	EN-DC FR1 SS-RSRP relative measurement accuracy	Rel-15	RE1_C001	UEs supporting EN-DC FR1	NOTE 1	
<b>4.7.1.2</b>	<b>Inter-frequency measurements</b>					
4.7.1.2.1	EN-DC FR1-FR1 SS-RSRP absolute measurement accuracy	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
4.7.1.2.2	EN-DC FR1-FR1 SS-RSRP relative measurement accuracy	Rel-15	RE1_C001	UEs supporting EN-DC FR1		
<b>4.7.2</b>	<b>SS-RSRQ</b>					
4.7.2.1	EN-DC FR1 SS-RSRQ measurement accuracy	FFS	FFS	FFS	NOTE 1	
4.7.2.2	EN-DC FR1-FR1 SS-RSRQ measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>4.7.3</b>	<b>SS-SINR</b>					
<b>4.7.4</b>	<b>L1-RSRP</b>					
4.7.4.1	EN-DC FR1 SSB-based L1-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	
4.7.4.2	EN-DC FR1 CSI-RS-based L1-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>4.7.5</b>	<b>SFTD</b>					

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
NOTE 1: The test case is incomplete.						

**Table 4.2-1a: Applicability of RRM EN-DC FR1 conformance test cases Conditions**

RE1_C001	IF (A.4.1-4/1 OR A.4.1-4/2 OR A.4.1-4/3 OR A.4.1-4/5) AND A.4.1-3/2 THEN R ELSE N/A
NOTE 1: The ICS proforma are defined in TS 38.508-2 [8].	

Table 4.2-2: Applicability of RRM EN-DC FR2 conformance test cases, ref. TS 38.533 [5]

Clause	TC Title	Release	Applicability		Additional Information (NOTE 3)	Branch
			Condition	Comment		
<b>5.3</b>	<b>RRC_CONNECTED state mobility</b>					
<b>5.3.2</b>	<b>RRC connection mobility control</b>					
<b>5.3.2.2</b>	<b>Random access</b>					
<b>5.4</b>	<b>Timing</b>					
<b>5.4.1</b>	<b>UE transmit timing</b>					
5.4.1.1	EN-DC FR2 UE transmit timing accuracy	FFS	FFS	FFS	NOTE 1	
<b>5.4.2</b>	<b>UE timer accuracy</b>					
<b>5.4.3</b>	<b>Timing advance</b>					
5.4.3.1	EN-DC FR2 timing advance adjustment accuracy	FFS	FFS	FFS	NOTE 1	
<b>5.5</b>	<b>Signaling characteristics</b>					
<b>5.5.1</b>	<b>Radio link monitoring</b>					
5.5.1.1	EN-DC FR2 radio link monitoring out-of-sync test for PSCell configured with SSB-based RLM RS in non-DRX mode	FFS	FFS	FFS	NOTE 1	
5.5.1.2	EN-DC FR2 radio link monitoring in-sync test for PSCell configured with SSB-based RLM RS in non-DRX mode	FFS	FFS	FFS	NOTE 1	
5.5.1.3	EN-DC FR2 radio link monitoring out-of-sync test for PSCell configured with SSB-based RLM RS in DRX mode	FFS	FFS	FFS	NOTE 1	
5.5.1.4	EN-DC FR2 radio link monitoring in-sync test for PSCell configured with SSB-based RLM RS in DRX mode	FFS	FFS	FFS	NOTE 1	
<b>5.5.2</b>	<b>Interruption</b>					
5.5.2.1	EN-DC FR2 interruptions at transitions between active and non-active during DRX in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
5.5.2.2	EN-DC FR2 interruptions at transitions between active and non-active during DRX in asynchronous EN-DC	FFS	FFS	FFS	NOTE 1	
5.5.2.3	EN-DC FR2 interruptions during measurements on deactivated NR SCC in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
5.5.2.4	EN-DC FR2 interruptions during measurements on deactivated NR SCC in asynchronous EN-DC	FFS	FFS	FFS	NOTE 1	
5.5.2.5	EN-DC FR2 interruptions during measurements on deactivated E-UTRAN SCC in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
5.5.2.6	EN-DC FR2 interruptions during measurements on deactivated E-UTRAN SCC in asynchronous EN-DC	FFS	FFS	FFS	NOTE 1	
<b>5.5.3</b>	<b>SCell activation and deactivation delay</b>					
5.5.3.1	EN-DC FR2 SCell activation and deactivation intra-band in non-DRX	FFS	FFS	FFS	NOTE 1	
<b>5.5.4</b>	<b>UE UL carrier RRC reconfiguration delay</b>					



<b>5.5.5</b>	<b>Beam failure detection and link recovery procedures</b>					
<b>5.5.6</b>	<b>Active BWP switch delay</b>					
<b>5.5.6.1</b>	<b>DCI-based and timer-based active BWP switch</b>					
5.5.6.1.1	EN-DC FR2 DCI-based DL active BWP switch in non-DRX in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
5.5.6.1.2	EN-DC FR2 DCI-based DL active BWP switch with SCell in non-DRX in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
<b>5.5.6.2</b>	<b>RRC-based active BWP switch</b>					
5.5.6.2.1	EN-DC FR2 RRC-based DL active BWP switch in non-DRX in synchronous EN-DC	FFS	FFS	FFS	NOTE 1	
<b>5.5.7</b>	<b>PSCell addition and release delay</b>					
<b>5.6</b>	<b>Measurement procedures</b>					
<b>5.6.1</b>	<b>Intra-frequency measurements</b>					
<b>5.6.2</b>	<b>Inter-frequency measurements</b>					
5.6.2.1	EN-DC FR2-FR2 event-triggered reporting in non-DRX	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
5.6.2.2	EN-DC FR2-FR2 event-triggered reporting in DRX	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
5.6.2.3	EN-DC FR2-FR2 event-triggered reporting in non-DRX with SSB time index detection	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
5.6.2.4	EN-DC FR2-FR2 event-triggered reporting in DRX with SSB time index detection	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
5.6.2.5	EN-DC FR1-FR2 event-triggered reporting in non-DRX	Rel-15	RE2_C002	UEs supporting EN-DC FR1 and FR2	NOTE 1	
5.6.2.6	EN-DC FR1-FR2 event-triggered reporting in DRX	Rel-15	RE2_C002	UEs supporting EN-DC FR1 and FR2	NOTE 1	
5.6.2.7	EN-DC FR1-FR2 event-triggered reporting in non-DRX with SSB time index detection	Rel-15	RE2_C002	UEs supporting EN-DC FR1 and FR2	NOTE 1	
5.6.2.8	EN-DC FR1-FR2 event-triggered reporting in DRX with SSB time index detection	Rel-15	RE2_C002	UEs supporting EN-DC FR1 and FR2	NOTE 1	
<b>5.6.3</b>	<b>L1-RSRP for beam reporting</b>					
5.6.3.1	EN-DC FR2 SSB-based L1-RSRP measurement in non-DRX	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
5.6.3.2	EN-DC FR2 SSB-based L1-RSRP measurement in DRX	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
5.6.3.3	EN-DC FR2 CSI-RS-based L1-RSRP measurement in non-DRX	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
5.6.3.4	EN-DC FR2 CSI-RS-based L1-RSRP measurement in DRX	Rel-15	RE2_C001	UEs supporting EN-DC FR2	NOTE 1	
<b>5.7</b>	<b>Measurement performance requirements</b>					
<b>5.7.1</b>	<b>SS-RSRP</b>					
5.5.7.1	EN-DC FR2 addition and release delay of known PSCell	FFS	FFS	FFS	NOTE 1	
5.7.1.1	EN-DC FR2 SS-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	
5.7.1.2	EN-DC FR2-FR2 SS-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>5.7.1.3</b>	<b>Inter-frequency measurements between FR1 and FR2</b>					

5.7.1.3.1	EN-DC FR1-FR2 SS-RSRP absolute measurement accuracy	FFS	FFS	FFS	NOTE 1	
5.7.1.3.2	EN-DC FR1-FR2 SS-RSRP relative measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>5.7.2</b>	<b>SS-RSRQ</b>					
<b>5.7.3</b>	<b>SS-SINR</b>					
<b>5.7.4</b>	<b>L1-RSRP for beam reporting</b>					
NOTE 1: The test case is incomplete.						
NOTE 2: Void.						
NOTE 3: For conformance testing involving FR2 test cases, the UE under test shall disable UL Tx diversity schemes.						

**Table 4.2-2a: Applicability of RRM EN-DC FR2 conformance test cases Conditions**

RE2_C001	IF (A.4.1-4/4 AND OR A.4.1-4/5) A.4.1-3/2 THEN R ELSE N/A
RE2_C002	IF A.4.1-4/5 AND A.4.1-3/2 THEN R ELSE N/A
NOTE 1: The ICS proforma are defined in TS 38.508-2 [8].	

Table 4.2-3: Applicability of RRM NR SA FR1 conformance test cases, ref. TS 38.533 [5]

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
<b>6.1</b>	<b>RRC_IDLE state mobility</b>					
<b>6.1.1</b>	<b>NR cell re-selection</b>					
6.1.1.1	NR SA FR1 cell re-selection	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.1.1.2	NR SA FR1-FR1 cell re-selection	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
<b>6.1.2</b>	<b>NR – E-UTRA cell re-selection</b>					
6.1.2.1	NR SA FR1 – E-UTRA cell re-selection to higher priority E-UTRA	Rel-15	RS1_C003	UEs supporting 5GS NR SA FR1 and E-UTRA		
6.1.2.2	NR SA FR1 – E-UTRA cell re-selection to lower priority E-UTRA	Rel-15	RS1_C003	UEs supporting 5GS NR SA FR1 and E-UTRA		
<b>6.2</b>	<b>RRC_INACTIVE state mobility</b>					
<b>6.3</b>	<b>RRC_CONNECTED state mobility</b>					
<b>6.3.1</b>	<b>Handover</b>					
6.3.1.1	NR SA FR1 handover with known target cell	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.3.1.2	NR SA FR1 handover with unknown target cell	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.3.1.3	NR SA FR1-FR1 handover with unknown target cell	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.3.1.4	NR SA FR1 – E-UTRA handover with known target cell	Rel-15	RS1_C003	UEs supporting 5GS NR SA FR1 and E-UTRA		
6.3.1.5	NR SA FR1 – E-UTRA handover with unknown target cell	Rel-15	RS1_C003	UEs supporting 5GS NR SA FR1 and E-UTRA		
<b>6.3.2</b>	<b>RRC connection mobility control</b>					
<b>6.3.2.1</b>	<b>RRC re-establishment</b>					
6.3.2.1.1	NR SA FR1 RRC re-establishment	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.3.2.1.2	NR SA FR1 - FR1 RRC re-establishment	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.3.2.1.3	NR SA FR1 - FR1 RRC re-establishment without serving cell timing	FFS	FFS	FFS	NOTE 1	
<b>6.3.2.2</b>	<b>Random access</b>					
6.3.2.2.1	Contention based random access test in FR1 for NR standalone	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.3.2.2.2	Non-Contention based random access test in FR1 for NR standalone	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
<b>6.3.2.3</b>	<b>RRC connection release with redirection</b>					
6.3.2.3.1	NR SA FR1 RRC connection release with redirection	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.3.2.3.2	NR SA FR1 – E-UTRA RRC connection release with redirection	Rel-15	RS1_C003	UEs supporting 5GS NR SA FR1 and E-UTRA	NOTE 1	
<b>6.4</b>	<b>Timing</b>					
<b>6.4.1</b>	<b>UE transmit timing</b>					
6.4.1.1	NR SA FR1 transmit timing accuracy	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
<b>6.4.2</b>	<b>UE timer accuracy</b>					
<b>6.4.3</b>	<b>Timing advance</b>					
6.4.3.1	NR SA FR1 timing advance adjustment accuracy	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
<b>6.5</b>	<b>Signalling characteristics</b>					
<b>6.5.1</b>	<b>Radio Link Monitoring</b>					
6.5.1.1	NR SA FR1 radio link monitoring out-of-sync test for PCell configured with SSB-based RLM RS in non-DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.5.1.2	NR SA FR1 radio link monitoring in-sync test for PCell configured with SSB-based RLM RS in non-DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.5.1.3	NR SA FR1 radio link monitoring out-of-sync test for PCell configured with SSB-based RLM RS in DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.5.1.4	NR SA FR1 radio link monitoring in-sync test for PCell configured with SSB-based RLM RS in DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.5.1.5	NR SA FR1 radio link monitoring out-of-sync test for PCell configured with CSI-RS-based RLM RS in non-DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.5.1.6	NR SA FR1 radio link monitoring in-sync test for PCell configured with CSI-RS-based RLM RS in non-DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.5.1.7	NR SA FR1 radio link monitoring out-of-sync test for PCell configured with CSI-RS-based RLM RS in DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.5.1.8	NR SA FR1 radio link monitoring in-sync test for PCell configured with CSI-RS-based RLM RS in DRX mode	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
<b>6.5.2</b>	<b>Interruption</b>					
6.5.2.1	NR SA FR1 interruptions during measurements on deactivated NR SCC	FFS	FFS	FFS	NOTE 1	
<b>6.5.3</b>	<b>SCell activation and deactivation delay</b>					
6.5.3.1	NR SA FR1 SCell activation and deactivation of known SCell in non-DRX for 160ms SCell measurement cycle	FFS	FFS	FFS	NOTE 1	
6.5.3.2	NR SA FR1 SCell activation and deactivation of known SCell in non-DRX for 320ms SCell measurement cycle	FFS	FFS	FFS	NOTE 1	
6.5.3.3	NR SA FR1 SCell activation and deactivation of unknown SCell in non-DRX	FFS	FFS	FFS	NOTE 1	
<b>6.5.4</b>	<b>UE UL carrier RRC reconfiguration delay</b>					
6.5.4.1	NR SA FR1 UE UL carrier RRC reconfiguration delay	FFS	FFS	FFS	NOTE 1	
<b>6.5.5</b>	<b>Link recovery procedures</b>					
6.5.5.3	NR SA FR1 CSI-RS-based beam failure detection and link recovery in non-DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.5.5.4	NR SA FR1 CSI-RS-based beam failure detection and link recovery in DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
<b>6.5.6</b>	<b>Active BWP switch delay</b>					

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
<b>6.5.6.1</b>	<b>DCI-based and timer-based active BWP switch</b>					
6.5.6.1.1	NR SA FR1 DCI-based DL active BWP switch in non-DRX	FFS	FFS	FFS	NOTE 1	
<b>6.5.6.2</b>	<b>RRC-based active BWP switch</b>					
6.5.6.2.1	NR SA FR1 RRC-based DL active BWP switch in non-DRX	FFS	FFS	FFS	NOTE 1	
<b>6.6</b>	<b>Measurement procedures</b>					
<b>6.6.1</b>	<b>Intra-frequency measurements</b>					
6.6.1.1	NR SA FR1 event-triggered reporting without gap in non-DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.1.2	NR SA FR1 event-triggered reporting without gap in DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.1.3	NR SA FR1 event-triggered reporting with gap in non-DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.1.4	NR SA FR1 event-triggered reporting with gap in DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.1.5	NR SA FR1 event-triggered reporting without gap in non-DRX with SSB index reading	Rel-15	RS1_C002	UEs supporting 5GS NR FDD SA FR1		
6.6.1.6	NR SA FR1 event-triggered reporting with gap in non-DRX with SSB index reading	Rel-15	RS1_C002	UEs supporting 5GS NR FDD SA FR1		
<b>6.6.2</b>	<b>Inter-frequency measurements</b>					
6.6.2.1	NR SA FR1-FR1 event-triggered reporting in non-DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.2.2	NR SA FR1-FR1 event-triggered reporting in DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.2.5	NR SA FR1-FR1 event-triggered reporting in non-DRX with SSB time index detection	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.2.6	NR SA FR1-FR1 event-triggered reporting in DRX with SSB time index detection	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
<b>6.6.3</b>	<b>Inter-RAT measurements</b>					
6.6.3.1	NR SA FR1 – E-UTRAN event-triggered reporting in non-DR	Rel-15	RS1_C003	UEs supporting 5GS NR SA FR1 and E-UTRAN		
6.6.3.2	NR SA FR1 – E-UTRAN event-triggered reporting in DRX	Rel-15	RS1_C003	UEs supporting 5GS NR SA FR1 and E-UTRAN		
<b>6.6.4</b>	<b>L1-RSRP for beam reporting</b>	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.6.4.1	NR SA FR1 SSB-based L1-RSRP measurement in non-DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.6.4.2	NR SA FR1 SSB-based L1-RSRP measurement in DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.6.4.3	NR SA FR1 CSI-RS-based L1-RSRP measurement in non-DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.6.4.4	NR SA FR1 CSI-RS-based L1-RSRP measurement in DRX	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
<b>6.7</b>	<b>Measurement performance requirements</b>					
<b>6.7.1</b>	<b>SS-RSRP</b>					
<b>6.7.1.1</b>	<b>Intra-frequency measurements</b>					

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
6.7.1.1.1	NR SA FR1 SS-RSRP absolute measurement accuracy	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
6.7.1.1.2	NR SA FR1 SS-RSRP relative measurement accuracy	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1		
<b>6.7.1.2</b>	<b>Inter-frequency measurements</b>					
6.7.1.2.1	NR SA FR1-FR1 SS-RSRP absolute measurement accuracy	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
6.7.1.2.2	NR SA FR1-FR1 SS-RSRP relative measurement accuracy	Rel-15	RS1_C001	UEs supporting 5GS NR SA FR1	NOTE 1	
<b>6.7.2</b>	<b>SS-RSRQ</b>					
6.7.2.1	NR SA FR1 SS-RSRQ measurement accuracy	FFS	FFS	FFS	NOTE 1	
6.7.2.2	NR SA FR1-FR1 SS-RSRQ measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>6.7.3</b>	<b>SS-SINR</b>					
<b>6.7.4</b>	<b>L1-RSRP for beam reporting</b>					
6.7.4.1	NR SA FR1 SSB-based L1-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	
6.7.4.2	NR SA FR1 CSI-RS-based L1-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>6.7.5</b>	<b>E-UTRAN RSRP</b>					
<b>6.7.6</b>	<b>E-UTRAN RSRQ</b>					
6.7.6.1	NR SA FR1 – E-UTRAN RSRQ measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>6.7.7</b>	<b>E-UTRAN RS-SINR</b>					
6.7.7.1	NR SA FR1 – E-UTRAN RS-SINR measurement accuracy	FFS	FFS	FFS	NOTE 1	
NOTE 1: The test case is incomplete.						

**Table 4.2-3a: Applicability of RRM NR SA FR1 conformance test cases Conditions**

RS1_C001	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/1 THEN R ELSE N/A
RS1_C002	IF A.4.1-1/1 AND A.4.1-3/1 THEN R ELSE N/A
RS1_C003	IF ((A.4.1-1/1 AND [10]A.4.1-1/2) OR (A.4.1-1/2 AND [10]A.4.1-1/2) OR (A.4.1-1/1 AND [10]A.4.1-1/2) OR (A.4.1-1/2 AND [10]A.4.1-1/2)) AND A.4.1-3/1 THEN R ELSE N/A
RS1_C004	IF (A.4.1-1/1 OR A.4.1-1/2) AND A.4.1-3/1 AND 4.3.2-1/9 THEN R ELSE N/A
NOTE 1: The ICS proforma are defined in TS 38.508-2 [8] unless otherwise stated.	

Table 4.2-4: Applicability of RRM NR SA FR2 conformance test cases, ref. TS 38.533 [5]

Clause	TC Title	Release	Applicability		Additional Information (NOTE 3)	Branch
			Condition	Comment		
<b>7.1</b>	<b>RRC_IDLE state mobility</b>					
<b>7.1.1</b>	<b>NR cell re-selection</b>					
7.1.1.1	NR SA FR2 cell re-selection	FFS	FFS	FFS	NOTE 1	
7.1.1.2	NR SA FR2-FR2 cell re-selection	FFS	FFS	FFS	NOTE 1	
<b>7.2</b>	<b>RRC_INACTIVE state mobility</b>					
<b>7.3</b>	<b>RRC_CONNECTED state mobility</b>					
<b>7.3.1</b>	<b>Handover</b>					
<b>7.3.2</b>	<b>RRC connection mobility control</b>					
<b>7.3.2.1</b>	<b>RRC re-establishment</b>					
7.3.2.1.1	NR SA FR2 RRC re-establishment	Rel-15	RS2_C001	UE supporting 5GS NR SA FR2	NOTE 1	
7.3.2.1.2	NR SA FR2 - FR2 RRC re-establishment	Rel-15	RS2_C001	UE supporting 5GS NR SA FR2	NOTE 1	
7.3.2.1.3	NR SA FR2 - FR2 RRC re-establishment without serving cell timing	FFS	FFS	FFS	NOTE 1	
<b>7.3.2.2</b>	<b>Random access</b>					
<b>7.3.2.3</b>	<b>RRC connection release with redirection</b>					
7.3.2.3.1	NR SA FR2 RRC connection release with redirection	FFS	FFS	FFS	NOTE 1	
<b>7.4</b>	<b>Timing</b>					
<b>7.4.1</b>	<b>UE transmit timing</b>					
<b>7.4.2</b>	<b>UE timer accuracy</b>					
<b>7.4.3</b>	<b>Timing advance</b>					
<b>7.5</b>	<b>Signalling characteristics</b>					
<b>7.5.1</b>	<b>Radio Link Monitoring</b>					
<b>7.5.2</b>	<b>Interruption</b>					
<b>7.5.3</b>	<b>Scell activation and deactivation delay</b>					
<b>7.5.4</b>	<b>UE UL carrier RRC reconfiguration delay</b>					
<b>7.5.5</b>	<b>Beam failure detection and link recovery procedures</b>					
7.5.5.1	NR SA FR2 SSB-based beam failure detection and link recovery in non-DRX	Rel-15	RS2_C001	UE supporting 5GS NR SA FR2	NOTE 1	
7.5.5.2	NR SA FR2 SSB-based beam failure detection and link recovery in DRX	Rel-15	RS2_C001	UE supporting 5GS NR SA FR2	NOTE 1	
7.5.5.3	NR SA FR2 CSI-RS-based beam failure detection and link recovery in non-DRX	Rel-15	RS2_C001	UE supporting 5GS NR SA FR2	NOTE 1	
7.5.5.4	NR SA FR2 CSI-RS-based beam failure detection and link recovery in DRX	Rel-15	RS2_C001	UE supporting 5GS NR SA FR2	NOTE 1	
<b>7.5.6</b>	<b>Active BWP switch delay</b>					
<b>7.5.6.1</b>	<b>Intra-frequency measurements</b>					
7.5.6.1.1	NR SA FR2 DCI-based DL active BWP switch in non-DRX	FFS	FFS	FFS	NOTE 1	

Clause	TC Title	Release	Applicability		Additional Information (NOTE 3)	Branch
			Condition	Comment		
7.5.6.1.2	NR SA FR1-FR2 DCI-based DL active BWP switch in non-DRX	FFS	FFS	FFS	NOTE 1	
<b>7.5.6.2</b>	<b>RRC-based active BWP switch</b>					
7.5.6.2.1	NR SA FR2 RRC-based DL active BWP switch in non-DRX	FFS	FFS	FFS	NOTE 1	
<b>7.6</b>	<b>Measurement procedures</b>					
<b>7.6.1</b>	<b>Intra-frequency measurements</b>					
7.6.1.1	NR SA FR2 event-triggered reporting without gap in non-DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.1.2	NR SA FR2 event-triggered reporting without gap in DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.1.3	NR SA FR2 event-triggered reporting with gap in non-DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.1.4	NR SA FR2 event-triggered reporting with gap in DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
<b>7.6.2</b>	<b>Inter-frequency measurements</b>					
7.6.2.1	NR SA FR2-FR2 event-triggered reporting in non-DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.2.2	NR SA FR2-FR2 event-triggered reporting in DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.2.3	NR SA FR2-FR2 event-triggered reporting in non-DRX with SSB time index detection	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.2.4	NR SA FR2-FR2 event-triggered reporting in DRX with SSB time index detection	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.2.5	NR SA FR1-FR2 event-triggered reporting in non-DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.2.6	NR SA FR1-FR2 event-triggered reporting in DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.2.7	NR SA FR1-FR2 event-triggered reporting in non-DRX with SSB time index detection	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.2.8	NR SA FR1-FR2 event-triggered reporting in DRX with SSB time index detection	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
<b>7.6.3</b>	<b>L1-RSRP for beam reporting</b>					
7.6.3.1	NR SA FR2 SSB-based L1-RSRP measurement in non-DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.3.2	NR SA FR2 SSB-based L1-RSRP measurement in DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.3.3	NR SA FR2 CSI-RS-based L1-RSRP measurement in non-DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
7.6.3.4	NR SA FR2 CSI-RS-based L1-RSRP measurement in DRX	Rel-15	RS2_C001	UEs supporting 5GS NR SA FR2	NOTE 1	
<b>7.7</b>	<b>Measurement performance requirements</b>					
<b>7.7.1</b>	<b>SS-RSRP</b>					
7.7.1.1	NR SA FR2 SS-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	



Clause	TC Title	Release	Applicability		Additional Information (NOTE 3)	Branch
			Condition	Comment		
7.7.1.2	NR SA FR2-FR2 SS-RSRP measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>7.7.1.3</b>	<b>Inter-frequency measurements between FR1 and FR2</b>					
7.7.1.3.1	NR SA FR1-FR2 SS-RSRP absolute measurement accuracy	FFS	FFS	FFS	NOTE 1	
7.7.1.3.2	NR SA FR1-FR2 SS-RSRP relative measurement accuracy	FFS	FFS	FFS	NOTE 1	
<b>7.7.2</b>	<b>SS-RSRQ</b>					
<b>7.7.3</b>	<b>SS-SINR</b>					
<b>7.7.4</b>	<b>L1-RSRP for beam reporting</b>					

NOTE 1: The test case is incomplete.  
NOTE 2: Void.  
NOTE 3: For conformance testing involving FR2 test cases, the UE under test shall disable UL Tx diversity schemes.

**Table 4.2-4a: Applicability of RRM NR SA FR2 conformance test cases Conditions**

RS2_C001	IF A.4.1-1/2 AND A.4.1-3/1 THEN R ELSE N/A
NOTE 1: The ICS proforma are defined in TS 38.508-2 [8] unless otherwise stated.	

**Table 4.2-5: Applicability of E-UTRA – NR Inter-RAT conformance test cases, ref. TS 38.533 [5]**

Clause	TC Title	Release	Applicability		Additional Information	Branch
			Condition	Comment		
NOTE 1: The test case is incomplete.						

---

## Annex A (informative): FFS

## Annex B (informative): Change history

Change history							
Date	Meeting	TDoc	CR	R ev	Cat	Subject/Comment	New version
2017-08	RAN5#76	R5-173911	-	-	-	Draft skeleton	0.0.1
2018-01	RAN5#1-5G-NR Adhoc	R5-180107	-	-	-	Updated after <a href="#">RAN5#1-5G-NR Adhoc</a> : - Foreword, scope, references, definitions, symbols and abbreviations, recommended test case applicability updated - Sub-clause 4.1.1, 4.1.2, 4.1.3 and 4.1.4 added - Change history added	0.1.0
2018-03	RAN5 #78	R5-181687	-	-	-	TP for Clause 4.1.1 Range 1 standalone conformance test cases	0.2.0
2018-03	RAN5 #78	R5-181688	-	-	-	TP for Clause 4.1.2 Range 2 standalone conformance test cases	0.2.0
2018-03	RAN5 #78	R5-181689	-	-	-	TP for Clause 4.1.3 NR interworking between NR range1 and NR range2 and between NR and LTE conformance test cases	0.2.0
2018-04	RAN5#2-5G-NR Adhoc	R5-182013	-	-	-	TP for Clause 3 Definitions, symbols and abbreviations	0.3.0
2018-04	RAN5#2-5G-NR Adhoc	R5-182047	-	-	-	TP for Clause 4 Recommended test case applicability	0.3.0
2018-08	RAN5#80	R5-185209	-	-	-	TP for Clause 4.1.1 of TS 38.522	1.0.1
2018-08	RAN5#80	R5-185210	-	-	-	TP for Clause 4.1.2 of TS 38.522	1.0.1
2018-08	RAN5#80	R5-185211	-	-	-	TP for Clause 4.1.3 of TS 38.522	1.0.1
2018-09	RAN#81	-	-	-	-	raised to v15.0.0 with editorial changes only	15.0.0
2018-12	RAN#82	R5-186501	0013	-	F	Applicability rules implementation in 38.522	15.1.0
2018-12	RAN#82	R5-188223	0015	-	F	Applicability for RRM NR tests	15.1.0
2018-12	RAN#82	R5-187566	0016	-	F	Update note in section 4.1 to include CBW and SCS in RF test applicability	15.1.0
2018-12	RAN#82	R5-187849	0014	1	F	Adding applicability for new 38.521-1 CA TCs	15.1.0
2018-12	RAN#82	R5-187881	0008	1	F	Update Clause 1 Scope of TS 38.522	15.1.0
2018-12	RAN#82	R5-187884	0011	1	F	TP for Clause 4.1.2 of TS 38.522	15.1.0
2018-12	RAN#82	R5-187922	0017	-	F	Removing FR2 test case 7.4 from TS 38.522 due to testability issue	15.1.0
2019-01	RAN#82	R5-187882	0009	1	F	Update Clause 3 of TS 38.522	15.1.1
2019-01	RAN#82	R5-187883	0010	1	F	TP for Clause 4.1.1 of TS 38.522	15.1.1
2019-01	RAN#82	R5-187885	0012	1	F	TP for Clause 4.1.3 of TS 38.522	15.1.1
2019-03	RAN#83	R5-191722	0021	-	F	addition of applicability for BFD and measurement	15.2.0
2019-03	RAN#83	R5-192507	0020	1	F	TP for TS 38.522	15.2.0
2019-03	RAN#83	R5-192508	0022	1	F	Addition of RRM Test Cases Applicability	15.2.0
2019-06	RAN#84	R5-195444	0027	1	F	TP for TS 38.522	15.3.0
2019-06	RAN#84	-	-	-	-	Administrative release upgrade to match the release of 3GPP TS 38.508-1 and TS 38.521-1 which were upgraded at RAN#84 to Rel-16 due to Rel-16 relevant CR(s)	16.0.0
2019-06	RAN#84	-	-	-	-	Addition of missing Table part of R5-195444 and part of a note.	16.0.1
2019-06	RAN#84	-	-	-	-	Formatted big tables to landscape	16.0.2
2019-09	RAN#85	R5-197650	0030	1	-	TP for TS 38.522	16.1.0
2019-09	RAN#85	R5-197650	0030	1	-	Added missing changes of R5-197650	16.1.1
2019-12	RAN#86	R5-199089	0032	2	-	TP for TS 38.522	16.2.0